

LED

4 ft. Single-Ended T8 Tube



FEATURES

- DLC® Part Number: PLTSP34213
- Suitable replacement for 32-Watt fluorescent T8 and T12 tubes
- Ballast Bypass
- NSF shatterproof coating ensures occupant safety
- Works with non-shunted lampholders
- UL listed for damp locations
- Has a Bi-Pin G13 base

TYPICAL APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Size	Lumens	Wattage	Kelvin	Operation	CRI	DLC?	Base	Warranty
PLT-90010	4 ft.	2100	18W	3500K	Ballast Bypass	82	YES	Medium Bi-Pin	5 Year

SPECIFICATIONS

BULB SHAPE	T8	LIFE HOURS	50,000
DIMMABLE	NO	FLUORESCENT EQUAL	32-WATT
SAFETY RATING	UL DAMP	COMPATIBILITY	BALLAST BYPASS
COLOR	HALOGEN WHITE	LAMPHOLDER(S)	NON-SHUNTED
LIFE HOURS	50,000	LENS	FROSTED GLASS
LUMENS PER WATT	117	LENGTH	48 IN.
VOLTAGE	120-277	DIAMETER	1 IN.