

LED

4 ft. Single-Ended T8 Tube



FEATURES

- Suitable replacement for 32-Watt T8 and 34 or 40-Watt T12 fluorescent tubes
- Ballast Bypass
- Works with non-shunted lampholders
- UL listed for damp locations
- Has a Bi-Pin G13 base
- DLC® Part Number: PLTSP34215

TYPICAL APPLICATIONS

- Office spaces and conference rooms
- Classrooms and hallways
- Hospitals and lobbies



SKU#	Size	Lumens	Wattage	Kelvin	Operation	CRI	DLC?	Base	Warranty
PLT-90012	4 ft.	2200	18W	5000K	Ballast Bypass	82	Yes	Medium Bi-Pin	5 Year

SPECIFICATIONS

BULB SHAPE	T8	FLUORESCENT EQUAL	32-WATT
DIMMABLE	NO	COMPATIBILITY	BALLAST BYPASS
SAFETY RATING	UL DAMP	LAMPHOLDER(S)	NON-SHUNTED
COLOR	DAYLIGHT WHITE	LENS	FROSTED GLASS
LED L70 LIFE HOURS	≥100,000	LENGTH	48 IN.
LUMENS PER WATT	122	DIAMETER	1 IN.
VOLTAGE	120-277		