

LED PAR 30

PARFECTION™ SERIES



PAR 30

Features and Benefits

- 50,000-hour life
- Up to 85% energy savings compared to halogen
- Dimmable down to 10%
- Thermal-Breeze™ heat sink technology
- Eco-Clear™ optics lens
- Instant-on, instant bright
- Attractive designs, fits in standard fixtures
- Reduces replacement and maintenance costs
- RoHS compliant
- 5-year warranty

Markets

- Restaurants
- Hospitality
- Retail
- Casinos
- Cinema

Applications

- Recessed Cans
- Track Lighting
- Shopping Malls
- Jewelry Stores
- Museums
- General Lighting
- Elevators

Litetronics LED PARFECTION™ Series Light Bulbs - The Greenest Lighting Solution from Litetronics

Litetronics LED PARFECTION™ series light bulbs save up to 85% on energy costs, and they are RoHS compliant with mercury-free and lead-free construction, making them the greenest replacement for halogen lighting. Their elegant style maintains the look and shape of an ordinary halogen PAR bulb, and they have the ability to throw a crisp, white beam of light to illuminate brilliant merchandise displays just like halogen bulbs. LED PARFECTION™ bulbs use a patent pending Eco-Clear™ optics lens that generates high center beam candle power in both 15 and 28-degree beam angles. Unlike halogen, LED PARFECTION™ bulbs do not generate ultraviolet, infrared light, or as much heat. This protects displayed items from fading colors and spoiling perishable items that are sensitive to heat.

Compared to competing LED PAR bulbs, LED PARFECTION™ bulbs have higher lumen output and maintain that advantage over their 50,000-hour rated life. This is due to the patent pending Thermal-Breeze™ heat sink design, which allows the LEDs to maintain optimum performance. LED PARFECTION™ bulbs do not need heavy metal heat sinks and actually weigh less than a standard halogen bulb because the Thermal-Breeze™ heat sink provides lower LED temperature to ensure optimum lumen maintenance - even inside recessed ceiling cans. LED PARFECTION™ bulbs' light weight will not exceed the weight capacity of existing fixtures and are less costly to ship.

LED PARFECTION™ light bulbs are dimmable with uniform, smooth, dimming control that works on most standard incandescent dimmers. LED PARFECTION™ bulbs can be turned on and off frequently without worrying about bulb life, and they turn on instantly with full lumen output. They are vibration-resistant. This provides improved reliability over CFL, halogen, and incandescent lighting.

LED PARFECTION™ bulbs drastically reduce maintenance and replacement costs, as well as landfill waste, with their 50,000-hour life. Perfectly designed, perfectly green, the Litetronics LED PARFECTION™ series solves all of your lighting challenges when replacing halogen reflector bulbs.

LITETRONICS®

4101 West 123rd Street
Alsip, Illinois 60803
www.Litetronics.com

LED PAR 30 PARFECTION™ SERIES



PAR 30

WATTS	BASE	VOLTS	DESCRIPTION	ORDERING CODE	BEAM ANGLE	BEAM SPREAD	QTY/ CASE	AVERAGE RATED LIFE	CRI ¹	CCT (K)	INITIAL LUMENS	C.B.C.P. ²	M.O.L.* ³	BONUS FEATURES
10	MED	120	10W PAR30 SP DIM	LP10562SP4D	15°	SPOT	6	50,000	83	3000	700	4,700	3.60"	4
10	MED	100-240	10W PAR30 SP	LP10562SP4	15°	SPOT	6	50,000	83	3000	700	4,700	3.60"	
10	MED	120	10W PAR30 FL DIM	LP10562FL2D	28°	FLOOD	6	50,000	83	2700	700	2,545	3.60"	4
10	MED	120	10W PAR30 FL DIM	LP10562FL4D	28°	FLOOD	6	50,000	83	3000	600	2,545	3.60"	4
10	MED	100-240	10W PAR30 FL	LP10562FL4	28°	FLOOD	6	50,000	83	3000	600	2,545	3.60"	
10	MED	120	10W PAR30 FL DIM	LP10562FL7D	28°	FLOOD	6	50,000	83	5000	825	3,000	3.60"	4
10	MED	120	10W PAR30 WF DIM	LP10562WF2D	40°	WIDE FLOOD	6	50,000	83	2700	700	1,000	3.60"	4
10	MED	120	10W PAR30 WF DIM	LP10562WF4D	40°	WIDE FLOOD	6	50,000	83	3000	700	1,000	3.60"	4
10	MED	120	10W PAR30 WF DIM	LP10562WF7D	40°	WIDE FLOOD	6	50,000	83	5000	825	1,180	3.60"	4

LED PARFECTION™ Series: Made-To-Order

WATTS	BASE	VOLTS	DESCRIPTION	ORDERING CODE	BEAM ANGLE	BEAM SPREAD	QTY/ CASE	AVERAGE RATED LIFE	CRI ¹	CCT (K)	INITIAL LUMENS	C.B.C.P. ²	M.O.L.* ³	BONUS FEATURES
5	MED	120	5W PAR30 FL	LP05562FL4	28°	FLOOD	6	50,000	83	3000	330	1,200	3.60"	
10	MED	120	10W PAR30 SP DIM	LP10562SP2D	15°	SPOT	6	50,000	83	2700	700	4,700	3.60"	4
10	MED	120	10W PAR30 SP DIM	LP10562SP6D	15°	SPOT	6	50,000	83	4100	800	5,030	3.60"	4
10	MED	120	10W PAR30 SP DIM	LP10562SP7D	15°	SPOT	6	50,000	83	5000	825	5,385	3.60"	4
10	MED	120	10W PAR30 FL DIM	LP10562FL6D	28°	FLOOD	6	50,000	83	4100	800	2,910	3.60"	4
10	MED	120	10W PAR30 WF DIM	LP10562WF6D	40°	WIDE FLOOD	6	50,000	83	4100	800	1,145	3.60"	4

COMPATIBLE DIMMERS

A list of compatible dimmers is available online at: litetronics.com/dimmers

CONVERSION CHART

LED	=	HALOGEN	=	INCANDESCENT
10-watt	=	50-watt	=	65-watt

Energy Star qualified

¹ +/- 3 points

² Center Beam Candle Power

³ Maximum Overall Length (in inches)

