

LED


Slim LED Downlight

PLT &



FEATURES

- Equipped standard with 0-10V continuous dimming driver that works with any standard 0-10V control/dimmer
- Double-sided frosted plate diffuses light and reduces glare
- CCT adjustable downlight features 2700K-3000K-4000K at the flip of a switch
- Ultra slim housing makes installation in cramped areas a breeze



SKU #

Kelvin

Lumens

Size

Wattage

Voltage

Life Hours

Warranty

PLT-50174

2700-3000-4000

580

4 in.

9

120

50000

3 years

FEATURES

- Uniform luminous surface
- Dimmable down to 10%

TYPICAL APPLICATIONS

- Office, Conference Rooms
- Homes, Hotels, Hospitals

WARRANTY

Warranty

3 Years

SPECIFICATIONS

Dimmable.....	Yes
DLC Listed.....	No
Safety Rating.....	ETL
CRI.....	90
Color.....	Warm, Halogen, and Cool White
Color Temp.....	2700-3000-4000 Kelvin
Life Hours.....	50,000
Wattage.....	9 Watt
Equivalence Wattage.....	50 Watt
Lumens.....	580
Voltage.....	120
Finish.....	White
Lens.....	Opaque
Outside Diameter.....	4.9 in.
Inside Diameter.....	3.2 in.
Height.....	0.71 in.
Weight.....	1.3 lbs.
Warranty.....	3 Years

DIMMER COMPATIBILITY

RECOMMENDED

MANUFACTURER	PART NO.	TYPE	MAX. PER DIMMER		
			7004	7004-4K	7006
LUTRON	DVELV-300P	ELECTRONIC LOW VOLTAGE	12	12	NC
LUTRON	SELV-300P	ELECTRONIC LOW VOLTAGE	12	12	NC
LEVITON	IPE04-1LZ	ELECTRONIC LOW VOLTAGE	12	12	12
LEVITON	No. 6615	ELECTRONIC LOW VOLTAGE	12	12	12
WATTSTOPPER	HDCL-453M	LED / CFL	12	12	12
LUTRON	SFTU-5A3P	FLUORESCENT	12	12	12
LUTRON	DVCL-153P	LED/CFL/INCANDESCENT	12	12	12
LUTRON	CTCL-153P	LED/CFL/INCANDESCENT	12	12	12