

LED

Slim LED Downlight



FEATURES

- Equipped standard with 0-10V continuous dimming driver that works with any standard 0-10V control/dimmer
- Double-sided frosted plate diffuses light and reduces glare
- CCT adjustable downlight features 2700K-3000K-4000K at the flip of a switch
- Ultra slim housing makes installation in cramped areas a breeze



SKU #

Kelvin

Lumens

Size

Wattage

Voltage

Life Hours

Warranty

PLT-50175

2700-3000-4000

900

6 in.

12

120

50000

3 years

FEATURES

- Uniform luminous surface
- Dimmable down to 10%

TYPICAL APPLICATIONS

- Office, Conference Rooms
- Homes, Hotels, Hospitals

WARRANTY

Warranty

3 Years

SPECIFICATIONS

Dimmable Yes
 DLC Listed No
 Safety Rating ETL
 CRI 90
 Color Warm, Halogen, and Cool White
 Color Temp 2700-3000-4000 Kelvin
 Life Hours 50,000
 Wattage 12 Watt
 Equivalence Wattage 60 Watt
 Lumens 900
 Voltage 120
 Finish White
 Lens Opaque
 Outside Diameter 6.7 in.
 Inside Diameter 4.9 in.
 Height 0.71 in.
 Weight 1.3 lbs.
 Warranty 3 Years

DIMMER COMPATIBILITY

RECOMMENDED

MANUFACTURER	PART NO.	TYPE	MAX. PER DIMMER		
			7004	7004-4K	7006
LUTRON	DVELV-300P	ELECTRONIC LOW VOLTAGE	12	12	NC
LUTRON	SELV-300P	ELECTRONIC LOW VOLTAGE	12	12	NC
LEVITON	IPE04-1LZ	ELECTRONIC LOW VOLTAGE	12	12	12
LEVITON	No. 6615	ELECTRONIC LOW VOLTAGE	12	12	12
WATTSTOPPER	HDCL-453M	LED / CFL	12	12	12
LUTRON	SFTU-5A3P	FLUORESCENT	12	12	12
LUTRON	DVCL-153P	LED/CFL/INCANDESCENT	12	12	12
LUTRON	CTCL-153P	LED/CFL/INCANDESCENT	12	12	12