



Compact Fluorescent PAR (Self-Ballasted)

The CFL PAR is considered the "bridge technology" between the Halogen PAR lamps and LED lighting. If your customers are interested in reducing energy, but not ready for an LED makeover, then CFL PARs with their 10,000 hour life and +40 lumens per watt output is a great choice to make.

✦ Features

- Available in PAR20, PAR30, PAR38
- Avg Rated Life: 10,000 hrs
- Energy Saving

CFL PAR20

Code	Description	Watt	Type	Base	Volt	Lumens	Incan Equiv.	MOL (in.)	Avr. Life (hr)	Color Temp
31200	CF9ET3/PAR20/SW	9	PAR20	E26	120	200	40W	4.0	10,000	2700K
31201	CF9ET3/PAR20/830	9	PAR20	E26	120	200	40W	4.0	10,000	3000K
31203	CF9ET3/PAR20/841	9	PAR20	E26	120	200	40W	4.0	10,000	4100K
31204	CF9ET3/PAR20/850	9	PAR20	E26	120	200	40W	4.0	10,000	5000K
31205	CF9ET3/PAR20/865	9	PAR20	E26	120	200	40W	4.0	10,000	6500K
31210	CF11PAR20/SW	11	PAR20	E26	120	230	50W	4.0	10,000	2700K
31211	CF11PAR20/830	11	PAR20	E26	120	230	50W	4.0	10,000	3000K
31213	CF11PAR20/841	11	PAR20	E26	120	230	50W	4.0	10,000	4100K

CFL PAR30

Code	Description	Watt	Type	Base	Volt	Lumens	Incan Equiv.	MOL (in.)	Avr. Life (hr)	Color Temp
31220	CF13PAR30/SW	13	PAR30	E26	120	600	55W	4.70	10,000	2700K
31221	CF13PAR30/830	13	PAR30	E26	120	600	55W	4.70	10,000	3000K
31222	CF13PAR30/835	13	PAR30	E26	120	600	55W	4.70	10,000	3500K
31223	CF13PAR30/841	13	PAR30	E26	120	600	55W	4.70	10,000	4100K
31224	CF13PAR30/850	13	PAR30	E26	120	600	55W	4.70	10,000	5000K
31225	CF13PAR30/865	13	PAR30	E26	120	600	55W	4.70	10,000	6500K
31230	CF15PAR30/SW	15	PAR30	E26	120	660	65W	4.70	10,000	2700K
31231	CF15PAR30/830	15	PAR30	E26	120	660	65W	4.70	10,000	3000K
31232	CF15PAR30/835	15	PAR30	E26	120	660	65W	4.70	10,000	3500K
31233	CF15PAR30/841	15	PAR30	E26	120	660	65W	4.70	10,000	4100K
31234	CF15PAR30/850	15	PAR30	E26	120	660	65W	4.70	10,000	5000K
31235	CF15PAR30/865	15	PAR30	E26	120	660	65W	4.70	10,000	6500K

CFL PAR38

Code	Description	Watt	Type	Base	Volt	Lumens	Incan Equiv.	MOL (in.)	Avr. Life (hr)	Color Temp
31240	CF20PAR38/SW	20	PAR38	E26	120	880	65W	5.10	10,000	2700K
31241	CF20PAR38/830	20	PAR38	E26	120	880	65W	5.10	10,000	3000K
31242	CF20PAR38/835	20	PAR38	E26	120	880	65W	5.10	10,000	3500K
31243	CF20PAR38/841	20	PAR38	E26	120	880	65W	5.10	10,000	4100K
31244	CF20PAR38/850	20	PAR38	E26	120	880	65W	5.10	10,000	5000K
31245	CF20PAR38/865	20	PAR38	E26	120	880	65W	5.10	10,000	6500K
31250	CF23PAR38/SW *	23	PAR38	E26	120	1050	75W	5.10	10,000	2700K
31251	CF23PAR38/830	23	PAR38	E26	120	1050	75W	5.10	10,000	3000K
31252	CF23PAR38/835	23	PAR38	E26	120	1050	75W	5.10	10,000	3500K
31253	CF23PAR38/841	23	PAR38	E26	120	1050	75W	5.10	10,000	4100K
31254	CF23PAR38/850	23	PAR38	E26	120	1050	75W	5.10	10,000	5000K

* These items are available by special order, minimum order quantity and lead times apply.

Shipping & Sales Exceptions

1. Green Energy Lighting Corp does not sell or ship Green Energy Lighting branded products containing Mercury into the States of Massachusetts, Maine and Vermont.
2. Green Energy Lighting Corp does not sell or ship Green Energy Lighting branded Compact Fluorescent lamps into the State of Washington.