



115 West Commercial Ave. Moonachie, NJ 07070

Dimmer Compatibility Guide

PLEASE NOTE: Compatibility is based upon testing conducted by the manufacturer in a controlled environment. Actual results may vary.

Product Family Name:	776775	776883	776890
Item Number:	LEDB25/27K/FL/3	LED/8640/27K/FL/M/3	LEDB25/30K/FL/3
Ordering Code:			
Item Number:			
Ordering Code:			

		Lamps per Dimmer						
Manufacturer	Product	Model Number	Overall Rating	Recommended Minimum	Maximum Tested*	Notes		
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	SummaTech	IP86	Best	1	6	Dimm down to 18%	
		SwitchUp	SE83-P	Best	1	6	Dimm down to 2%	
	Lutron	Vista	VPO6-ILZ	Good	2	6	Dimm down to 7%	
		Taggler	TG-600	Best	1	6	Dimm down to 10%	
	Cora	Dayark	DL-600	Best	1	6	Dimm down to 1%	
		Dayark	S-600	Best	1	6	Dimm down to 1%	
	Legrand	Maestro	MAW-600	Best	2	6	Dimm down to 6%	
		Titan	CD703-PW	Best	1	6	Dimm down to 20%	
	Harmony	CD703-PTC	Best	1	6	6	Dimm down to 1%	
		Harmony	H703-PTC	Best	1	6	Dimm down to 3%	
CFL/LED	Leviton	SummaTech	IP06	Best	1	6	Dimm down to 2%	
		EuroSlide	SE74	Best	1	6	Dimm down to 10%	
	Decora	DE72	Best	1	6	Dimm down to 8%		
		Dayark	DS06-ILZ	Best	1	6	Dimm down to 10%	
	Lutron	Dayark	DLCL153	Best	1	6	Dimm down to 1%	
		Dayark	DLCL153PL	Best	1	6	Dimm down to 1%	
	Maestro	MAEL153MLH	Best	1	6	Dimm down to 7%		
		Dayark	DLCL153P	Best	1	6	Dimm down to 1%	
	Taggler	TGCL153PH	Best	2	6	Dimm down to 1%		
		Radio RA	RA2RH-ILCL-PD	Best	1	6	Dimm down to 5%	
	Legrand	Harmony	DCL483-PTC	Best	1	6	Dimm down to 7%	
		Harmony	HCL483-PTC	Best	1	6	Dimm down to 1%	
	Adorne Paddle	ADPDS15LM2	Bad	1	6	Dimm down to 18%		
	Electronic Low Voltage	Leviton	Vista	VPO6	Best	1	6	Dimm down to 13%
			SummaTech	PE84	Best	1	6	Dimm down to 10%
Decora		DE15-P	Bad	1	6	Dimm down to 42%		
		Dayark Countour	CTELV-30SP	Best	1	6	Dimm down to 10%	
Lutron		Dayark	DVCL153PL	Best	1	6	Dimm down to 10%	
		Maestro	MAELV-600	Best	1	6	Dimm down to 10%	
Dayark		SILV8-30SP	Best	1	6	Dimm down to 10%		
		WREN	WREN-80MM-W	Best	1	6	Dimm down to 10%	
Legrand		Scene Director	SE1V	Bad	1	6	Dimm down to 27%	
		Dayark	CTELV-30SP	Best	1	6	Dimm down to 10%	
Magnetic Low Voltage	Leviton	Vista	VPM-06	Best	2	6	Dimm down to 9%	
		Decora	DE15-P	Best	1	6	Dimm down to 4%	
	Lutron	Maestro	MALV-600	Best	2	6	Dimm down to 7%	
Legrand	Harmony	DLV703-PW	Best	1	6	Dimm down to 1%		
	Titan	CDLV703-PW	Best	1	6	Dimm down to 20%		
Smart Dimmer	Leviton	Decora Digital (Bluetooth)	DDMK1-8LZ	Best	1	6	Dimm down to 18%	
	Leviton	Decora Smart 2-Wire Technology	D2HD	Best	1	6	Dimm down to 15%	
	Lutron	Caseta Wireless smart dimmer Wi-Fi	PD-28WD	Best	1	6	Dimm down to 23%	
	Lutron	Caseta Wireless smart dimmer Wi-Fi	PD-8VCL	Best	1	6	Dimm down to 7%	
	Legrand	Adorne Touch Wi-Fi TRU Universal	ADTFT08MTLW1	Best	1	6	Dimm down to 1%	
Legrand	Adorne Soft Tap Wi-Fi TRU Universal	ADTFT08MTLW1	Best	1	6	Dimm down to 1%		
EE	2-WAVE	2WAVE	Best	1	6	Dimm down to 1%		
Universal	Legrand	Adorne SoftTap	ADTFT03TU	Good	1	6	Dimm down to 24%	
		Miss Delamater	MDK-W	Good	1	6	Dimm down to 2%	
	Harmony	H703PLTC	Good	1	6	Dimm down to 2%		
	Adorne Whisper	ADW703MMTLW2	Best	1	6	Dimm down to 2%		
	Adorne Touch	ADTFT03MMTLW2	Best	1	6	Dimm down to 3%		
Cooper	Dimmer	DL08P-CFL-L	Good	1	6	Dimm down to 1%		
Day	SAL08P-W-K-L	Good	1	6	Dimm down to 1%			

*Maximum Tested Lamps per Dimmer: Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer. Only equipment "yes or" lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating

Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dba), wide dimming range - can dim down to 20% or less of light output.
High End (H.E.) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.
Low End (L.E.) Dead Travel	

Contact Information:
 Bulbrite Industries Inc.
 115 West Commercial Avenue Moonachie, New Jersey 07070
 PHONE: 1-800-528-5555
 FAX: 2-01-461-7108
 Email: Productsupport@bulbrite.com
 ©2019 Bulbrite Industries Inc.
 All Rights Reserved.