



Contractor Select™

TWS LED

Wall Pack

Our new "traditional-style" LED luminaires offer the shapes you've grown accustomed to coupled with the highpowered, energy-efficient LEDs you want. This fixture was designed to fit seamlessly – eliminating unwanted markings from the removal of older fixtures. Replace one or replace them all, either case, with energy savings of up to 80%, Lithonia has you covered.

FEATURES:

- Replaces up to 100W Metal Halide, saves 80% energy
- Traditional form factor, and payback within two years
- Photocell for dusk to dawn operation



Catalog Number	UPC	Description	Replaces Up To	Lumens	Wattage	CCT	Voltage	Finish	Pallet qty.
TWS LED P1 50K MVOLT PE DDB M4	191723952063	WALL PACKS	100 METAL HALIDE / 70 HIGH PRESSURE SODIUM	2,124	18W	5000K	120-277V	DARK BRONZE	144

Accessories: <i>Order as separate catalog number.</i>	
TWSWG U	Wire guard accessory



Specifications

INTENDED USE:

For entrances, stairwells, corridors, other pedestrian areas.

CONSTRUCTION:

Cast aluminum backplate on which electrical components are mounted for maximum heat-dissipation. Gasketing between backplate and front cover prevents the entry of water and contaminants. External hardware includes phillips head and tamper-proof hex-head fasteners.

ELECTRICAL:

35W-70W HPS use 120V normal power factor.

Porcelain, medium-base socket with copper alloy nickel-plated screw shell and center contact. UL listed 660W, 600V, 4KV pulse rated. Medium-base lamp included with the fixture.

INSTALLATION

Units are for wall mounting and include two 3/4" knockouts for routing electrical conduit.

LISTINGS:

UL listed for wet locations. Listed and labeled to comply with Canadian Standards.

DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

WARRANTY:

5-year limited warranty. Complete warranty terms located at:

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Dimensions

TWS LED WALL PACK

Height: 10-7/8" (27.9cm)

Width: 6-3/4" (16.5cm)

Depth: 5-5/16" (13.3cm)

Weight: 3.19 lbs (2.2 kgs)

All dimensions are inches (centimeters) unless otherwise indicated.

