

3



Item#: 55641 LED 48" STRIP FIXTURE LED READY FIXTURE

FEATURES

- Use 30% less energy than a traditional fluorescent fixture
- · Die formed, and rigidly fabricated
- · LED ready with non-shunted sockets
- Pre-wired at both ends
- Works with both Single-End and Double-End Direct
 Wire lamps
- Designed for surface or chain mounting

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Т8
2
120-277V
-4° ~ 122°F
DAMP
IP40
-

CONSTRUCTION

Warranty (Years)

Housing	22 Gauge C.R.S
Base / Power Supply	Hard Wired
Finish	High Gloss Baked White Enamel

QUALIFICATIONS

Pending

Operating temperature may vary depending on the lamps used. - Specifications are subject to change without notice.

LED 48" STRIP FIXTURE



DIMENSIONS (Inches)

Length	48"
Width	4.4"
Height	2.1"
Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)		
Product Sheet	VIEW	
Install Instructions	VIEW	

۲	48"	

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768024968	49.2" x 4.6" x 2.3"	5.5
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
55641	LED 48" STRIP FIXTURE FOR 2 T8/DE - SUPERIOR LIFE®	1

ACCESSORIES

54896	360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30' DIA, 8-40' HEIGHT 800W/1200W • 120/277V - SUPERIOR LIFE®	50
54894	EXTENDER MOUNT FOR SENSOR 54896/54897/54898 - SUPERIOR LIFE®	100
45005	WIRE GUARD FOR 4' STRIP FIXTURE/WHITE	1
55004	WHITE REFLECTOR FOR 4' OR 8' STRIP FIXTURE	1

ADDITIONAL INFORMATION:

• Pairs with Superior Life® Direct Wire Single-End or Double-End UL Type B Lamps. Follow specific lamp installation wiring instructions for correct wiring.