# LED Wall Pack Light Instruction

#### Application:

Available in industrial lighting, landscape lighting, courtyard, building, hotel, building exterior, etc.

#### Caution:

- 1.Do not use an electric generator to test this fixture.
- 2.Please abide by related country, regional and local law and regulations when installing this fixture.
- 3.Please don't install the fixture when raining to lower the risk of electric shock and avoid failure.


#### Note:

- 1. To avoid the possibility of electrical shock or fire, the installation personnel must have professional electric knowledge.
- 2. Please wear gloves to avoid injury before installation.
- 3. If any smoke or spark of the wire occurs, please turn off the power immediately and notify relevant personnel.

#### Installation I:


1. Turn off the power

2. Loosen the 4 screws



3. Remove the 1/2 end cap

- 4. Peel off the yellow sticker and paste it on the round area of the bottom plate



Any further questions or interests, please visit

## www.pltsolutions.com


Any further questions or interests, please visit

www.pltsolutions.com




### Installation Instruction


5. Fix the bottom plate on the round plate




7.Reattach the fixture with 4 screws.



6.Securely make appropriate wiring connections.




8.Once the above connections are made, turn on the power.




#### Installation II:


1. Turn off the power



3. Paste the black sponge pad on the bottom plate








Any further questions or interests, please visit


#### www.pltsolutions.com

### Installation Instruction


5.Remove one of the 1/2 end caps and pull supply conductors through the hole.




7. Return on the fixture to the bottom plate and tighten it with screws




6.Securely make appropriate wiring connections.



8.Turn on the power after good wiring and insulation are ensured.



Note:Be sure to select the desired CCT by sliding the dip switch once the bottom plate is secured to the wall.



DIM+:Purple DIM-:Gray

3000K 4000K 5000

#### Standard wire: L/live wire:Black\Brown; N/null wire:White\Blue; Ground wire:Green\Yellow-green.

# Warning/Avertissement:

MIN 90°C SUPPLY CONDUCTORS

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

#### LES FILS D'ALIMENTATION 90 °C MIN


CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS.



Any further questions or interests, please visit

## www.pltsolutions.com

# 2. Loosen the 4 screws



4. Screw the bottom plate on the wall