



65W
REPLACEMENT

90+
CRI

9W
Watts

E26

120V
Voltage

DAMP LOCATION

Dimmable

High quality of light and color rendering (90+ CRI, 50+ R9),
with low flicker, flicker <30%,
Smooth dimming. Dimming lower than 10%.





ELECTRICAL SPECIFICATIONS

MODEL NO.	LUMEN	POWER	CCT	BEAM	CRI	PF	CBCP
SE-RCU02.1111-B	810LM	9W	2700K	110°	>90	>0.9	-

MECHANICAL SPECIFICATIONS

MODEL NO.	MEASURES	WEIGHT	OPERATIONAL TEMPERATURE	INNER BOX QTY	MASTER CARTON QTY
SE-RCU02.1111-B	3.74in X 5.1in	3.7oz	-20°C - 40°C	6pcs	12pcs






RA – CHART: >90

RA refers to the average value of R1 to R8.

R9 is the score that represents how accurately a light source will reproduce strong red colors. "Accurate" is defined as similarity to daylight or incandescent bulbs, depending on the color temperature.

R VALUES						
R1=93	R2=98	R3=97	R4=92	R5=94	R6=97	R7=89
R8=79	R9=57	R10=96	R11=94	R12=88	R13=95	R14=99



TM30 GRAPHIC

TM-30 deals with the color rendition of object.

R_f - a fidelity index that is similar to the commonly used CRI

R_g - a gamut index that provides information about saturation

Color vector graphic- a graphical representation of hue and saturation relative to a reference source.

