5 West Commercial Ave.							
nachie, NJ 07074			Dimmer Compatibility Gui	de			
		PLEASE NOTE: Compatibility list	is based upon testing conducted by the manufacturer in a lab sim				
oduct Family Name: m Number: dering Code: m Number: dering Code:	773220 LED14JBOXDL/6/827/WHRD/D	773221 LED14JBOXDL/6/830/WHRD/D	773222 LED14JBOXDL/6/840/WHRD/D			_	
					Lamps pe Recommended Minimum	r Dimmer Maximum Tested*	
	Manufacturer	Product	Model Number	Overall Rating	Recommended Minimum	6	Notes Dims down to 129
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	SureSlide	6633-P	Good Best	1	6	Dims down to 6%
		Vizia	VPI06-1LZ TG-600	Good Good	2	6	Dims down to 6% Dims down to 129
	Lutron	Toggler Diva	DV-600	Best	1	6	Dims down to 3%
		Skylark	S-600	Best	1	6	Dims down to 5%
	Legrand	Maestro Titan	MAW-600 CD703-PW	Good Good	2	6	Dims down to 3% Dims down to 159
		Harmony	D703-PTC	Best	1	6	Dims down to 3%
		Harmony	H703-PTC	Best	1	6	Dims down to 8%
CFL/LED		IllumaTech	IPL06	Best	1	6	Dims down to 2%
	Leviton	Sureslide	6674	Best	1	6	Dims down to 109
		Decora Decora Slide	6672 DSL06-1LZ	Good Best	1	6	Dims down to 129 Dims down to 109
	Lutron	Skylark	CTCL-153	Best	1	6	Dims down to 109 Dims down to 1%
		Diva	DVCL-153PL	Best	1	6	Dims down to 1%
		Maestro Skylark	MACL-153MLH SCL-153P	Best Best	1	6	Dims down to 6% Dims down to 1%
		Toggler	TGCL-153PH	Best	1	6	Dims down to 1%
		Radio RA	RA2RR-6CL-PD	Best	1	6	Dims down to 5%
	Legrand	Harmony Harmony	DCL453-PTC HCL453PTC	Best Best	1	6	Dims down to 5% Dims down to 109
		Adorne Paddle	ADPD453LM2	Bad	1	6	Dims down to 25%
		h.a					
Electronic Low Voltage	Leviton	Vizia IllumaTech	VPE04 IPE04	Best Best	1	6	Dims down to 109 Dims down to 7%
		Decora	6615-P	Bad	1	6	Dims down to 309
	Lutron	Skylark Countour	CTELV-303P	Best	1	6	Dims down to 109
		Diva Maestro	DVELV-300P MAELV-600	Best Best	1	6	Dims down to 109 Dims down to 109
		Skylark	SELVB-300P	Best	1	6	Dims down to 109
-	Learner	VIERTI	VTEL-600M-W SCELV	Good	1	6	Dims down to 209
	Legrand	Scene Director			1	6	
Magentic Low Voltage	Leviton	Vizia	VPM-06	Good	2	6	Dims down to 5%
	Lutron	Decora Maestro	6613-P MALV-600	Best Good	1 4	6	Dims down to 8% Dims down to 5%
	Lution	Harmony	DLV703-PW	Best	1	6	Dims down to 5%
	Legrand	Titan	CDLV703-PW	Good	1	6	Dims down to 139
Smart Dimmer	Leviton	Decora Digital (Bluetooth)	DDMX1-BLZ	Good	1	6	Dims down to 149
	Leviton	Decora Smart Z-Wave Technology	DZ6HD	Best	1	6	Dims down to 109
	Leviton	Decora Smart Wi-Fi Technology	DW1KD PD-10NXD	Best	1	6	Dims down to 109 Dims down to 8%
	Lutron	Caseta Wireless smart dimmer Wi-Fi Caseta Wireless smart dimmer Wi-Fi	PD-10NXD PD-6WCL	Best Best	1	6	Dimsdown to 9%
	GE	Z WAVE	ZW3005	Best	1	6	Dims down to 2%
Universal		Adorno Softan	ADTR702TU	Cood	1	6	Dime down to 159
	Legrand	Adorne SofTap Miro Decorator	DRD4-W	Best	1	6	Dims down to 159 Dims down to 2%
		Harmony	H703PTUTC	Good	1	6	Dims down to 209
					1		Dims down to 2% Dims down to 2%
	Conner	Decorator	DAL06P-C2-K-L	Best	1	6	Dims down to 2%
	Cooper	Skye	SAL06P-W-K-L	Best	1	6	Dims down to 2%
Maximum Tested (Lamps per Dimmer) - Add May experience "pop-on", lights cannot be tr	GE Legrand Cooper itional lamps may work with your dimmer r	Z WAVE Adorne SofTap Miro Decorator Harmony Adorne Whisper Adorne Touch Decorator	ADTP703TU DR04-W H703PTUTC ADWR700MMTUW2 ADTH700MMTUW2 DAL06P-C2-K-L SAL06P-W-K-L mer manufacturer. um light level for the lights to first turn on if they	Best Good Best Good Best Best Best	1 1 1 1 1 1 1 1	6 6 6 6 6 6 6	Dims dow Dims dow Dims dow Dims dow Dims dow Dims dow Dims dow
se midany on. Then, the sider can be lowe	ered to get to a lower light level, the dimini	a cannot be tarried on to just the minimum rever.					
verall Rating							
			t audible noise, no dimming range, does not tur audible noise may be present, dimming not smo				
					other form of control button) is moved	d without affecting the light l	evel These periods of d
ti	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of deat travel are minor and most of the time not visible. Minor audible noise.						
st N	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output.						
	Determines how much, if any, dead trav	el exists at the top and bottom of the dimm	er's range. Dead travel is when the slider can be	e moved without affecting the light	level.		
ich End (H.E.) Dood Troug	*	· · · · · · ·			level.		
utact Information: ulbrite Industries Inc. IS West Commercial Avenue oonachie, New Jersey 07074 (Net : 1-800-528-555 N: 1-800-454-7708 N: 1-800-454-7708							