

DesignLights Consortium



Model Number	PLTBG321
Product ID	PLQDLGMNQ11A
QPL	Solid State Lighting
Manufacturer	Precision Lighting & Transformer, Inc
Brand Name	PLT
Primary Use	Replacement Lamps for Outdoor Pole/Arm-mounted Decorative Luminaires (Type B)
DLC Family Code	CCCHOW
Listing Status	Listed
Date Qualified	2021-07-19

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Product ID Unique ID for each product	PLQDLGMNQ11A
Manufacturer Product Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTBG321
Classification QPL Listing Status (Standard/Premium)	Standard
Parent Determines whether a listed product is a Parent (Tested Data)	No
DLC Family Code Unique ID for each product family	CCCHOW
Technical Requirements Version DLC Technical Requirements Version	5.1
Luminaire Length Reported Product length from manufacturer provided specification sheet in feet, applicable to linear ambient luminaires and linear replacement lamps only	0.73 ft
Input Power Type Type of input power that can be supplied to the product (AC, DC, or POE) from manufacturer provided specification sheet	AC

PRODUCT CATEGORIZATION VIEW DETAILS

--	--

CategoryMost general product characterization (indoor, outdoor, luminaire, retrofit, lamp)	Mogul (E39) Screw-Base Replacements for HID Lamps
General ApplicationOverall type of product (2nd level product characterization)	Low Output
Primary Use DesignationSpecific type of product (3rd level product characterization)	Replacement Lamps for Outdoor Pole/Arm-mounted Decorative Luminaires (Type B)

PRODUCT CAPABILITIES VIEW DETAILS

Integral ControlsCapability of a control to be embedded within the product from manufacturer provided specification sheet	No
Dimming Capability and RangeAbility of product change light level via dimming and to what minimum level from manufacturer provided specification sheet	Continuous Dimming above 10%
Sensor TypeList of all Sensor types available with product from manufacturer provided specification sheet	No Sensor
Wired Communication ProtocolList of all wired communication protocols available with product from manufacturer provided specification sheet	0-10V
Wireless Communication ProtocolList of all wireless communication protocols available with product from manufacturer provided specification sheet	RF
Field Adjustable Light Output	TRUE
White-TunableAbility of product to adjust CCT output from manufacturer provided specification sheet	No
Warm-DimmingCapability of product to increase CCT output as light output is dimmed from manufacturer provided specification sheet	No
Field Adjustable Light DistributionCapability of product whose light distribution can be intentionally adjusted from the default factory	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light OutputManufacturer Reported Light Output	4143.3 lm
---	-----------

Reported Efficacy (AC)Manufacturer Reported Efficacy (AC)	120.41 lm/W
Reported CCTManufacturer Reported CCT	3000 K
Reported CRI (Ra)Manufacturer Reported CRI (Ra)	82.5
Reported R9Manufacturer Reported R9	8
Reported IES Rf	84
Reported IES Rg	94
Reported IES Rcs,h1	-12
Reported Default Light OutputManufacturer reported Light output as shipped (Dimmable or field adjustable light output only)	4143.3 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input WattageManufacturer Reported Wattage	34.41 W
Reported Total Harmonic DistortionManufacturer Reported Total Harmonic Distortion	23.11 %
Reported Power FactorManufacturer Reported Power Factor	0.885
Reported Default Input Wattage	34.41

VERSION HISTORY VIEW DETAILS

2021-07-19	Listed	5.1	Standard
------------	--------	-----	----------