Reduce energy costs by replacing halogen PAR38 bulbs in your recessed and track lighting with these more efficient LED PAR38 bulbs.

# FEATURES

Efficiently replaces a 120W halogen PAR38 bulb

LED PAR38

- Standard household medium (E26) base
- Dimmable; see dimmer compatibility sheet for a full list of dimmers

# LISTINGS

- UL Listed for wet locations
- FCC
- RoHS

## PERFORMANCE


- CRI: 80
- CCT: 5000K
- Rated Lifetime L70: 15,000 hours

#### WARRANTY

• 1 year limited warranty; see pltsolutions.com for warranty details

### APPLICATIONS

- Track Lights
- Recessed Cans







	Power Consumption	15 Watt			
PERFORMANCE	Lumens	1250			
	Efficacy (LPW)	83			
	CRI	80			
	Beam Angle	40 Degrees			
	ССТ	5000K			
	Life (L70)	15000			
ELECTRICAL	Input Voltage	120V			
	Shape	PAR38			
CONSTRUCTION	Base	E26			
	Finish	Frosted			
	Certifications	UL Listed; FCC			
LISTINGS	Material Usage	RoHS – No mercury or lead			
	Environment	Wet Location Rated			

# PLTS-12098

## PERFORMANCE SUMMARY

ltem #	Shape	Lumens	Wattage	LPW	Voltage	Replaces	ССТ	CRI	Finish	Life/ Hours	Dimmable
PLTS-12098	PAR38	1250	15	83	120V	120W Halogen	5000K	90	Frosted	15000	Yes

#### DIMENSIONS



DIMENSIONS

Height: 5.12" Diameter: 4.72"

#### DIMMER COMPATIBILITY

Lutron MACL-153M-WH, DVCL-153P-WH, PD-6WCL-WH-P, CTCL-153PDH-WH, P-PKG1W-WH, P-PKG1W-WH-R, DIVA DVELV-300P-WH, NLV-1000-LA, SKYLARK SLV-600P-WH, RADIORA2 RRD-6CL-WH, CL DIMMER TOGGLER, CASEFA WIRELESS, DIVA CL, DSL06-001-1LZ, 06674-002-10W, RDL06-001-10Z, DSE06-001-10Z, DDMX1-011-BLZ, DDE06-BLZ 600W

#### Olegrand RHCL453PW

Leviton NO.6674 600W, NO.6672 600W, NO.IPL06 600W, MACL-153MH-WH, TGCL-153P-WH, DVCL-153PR-WH, DW6HD-1BZ, SLIDE DIMMER, SLIDE DIMMER 3WAY, NO.IPL06 R50-IPL06-10M

Martin Jerry MJ-SD01

TP Link Kasa Smart HS220

#### WARNINGS

- Only use this LED PAR38 bulb with the dimmers listed in the compatibility list. Using this bulb with incompatible dimmers may cause performance issues including humming, buzzing, flickering, and poor dimming performance.
- Not rated for use in enclosed fixtures.