



Pro Line Family of LED Lamps

Product Specifications



For an affordable LED upgrade, switch to TCP's PRO line LED Lamps. PRO line LEDs are available in multiple options from A-Lamps, to BR30 and PAR38 lamps. See how you can maximize savings and minimize maintenance cost with Pro LEDs.

Reasons to choose the PRO Line from TCP

- Long life: 15,000 hours minimizes replacement and maintenance costs
- Inexpensive alternative for cost-sensitive projects
- ANSI Construction Compliant to fit most general applications
- UL approved for damp location means lamps can be used outdoors when protected from the elements. (All PAR lamps are suitable for wet locations.)

Ideal Applications

- Commercial
- Retail
- Industrial
- Residential

Specifications:

Input Line Voltage	120 VAC	CRI	80
Input Line Frequency	50/60HZ	Warranty	3 Years
Lamp Life (Rated)	15,000 hours	* All A-Lamps, Deco, and R/BR Floods are approved for use in Enclosed Luminaires	
Minimum Starting Temp	-22F/-30C	* Pars are not recommended for use in Enclosed Luminaires	
Maximum Operating Temp	40°C		



Specifications:



ITEM #	DESCRIPTION	WATTS	INCAND. WATTS	CRI	LUMENS	LPW	COLOR	FINISH	HOURS	MOL (inches)	DIA (inches)	BASE	WARRANTY YEARS
LED All Glass A-LAMP • 15,000 Hour													
4.5W A19 • Dimmable													
LFF40A19D1527K	LED 40W EQ GLASS A19 DIM 27K FR	4.5	40	80	425	94.4	2700K	FROST	15,000	4.2	2.4	E26	3
LFC40A19D1527K	LED 40W EQ GLASS A19 DIM 27K CL	4.5	40	80	425	94.4	2700K	CLEAR	15,000	4.2	2.4	E26	3
5W A19 • Non-Dimmable													
LFF40A19N1527K	LED 40W EQ GLASS A19 ND 27K FR	5	40	80	425	85.0	2700K	Frosted	15,000	4.2	2.4	E26	3
LFF40A19N1550K	LED 40W EQ GLASS A19 ND 50K FR	5	40	80	425	85.0	5000K	Frosted	15,000	4.2	2.4	E26	3
LFC40A19N1527K	LED 40W EQ GLASS A19 ND 27K CL	5	40	80	425	85.0	2700K	Clear	15,000	4.2	2.4	E26	3
LFC40A19N1550K	LED 40W EQ GLASS A19 ND 50K CL	5	40	80	425	85.0	5000K	Clear	15,000	4.2	2.4	E26	3
8W A19 • Dimmable													
LFF60A19D1527K	LED 60W EQ GLASS A19 DIM 27K	8	60	80	725	90.6	2700K	Frosted	15,000	4.2	2.4	E26	3
LFF60A19D1550K	LED 60W EQ GLASS A19 DIM 50K	8	60	80	725	90.6	5000K	Frosted	15,000	4.2	2.4	E26	3
LFC60A19D1527K	LED 60W EQ GLASS A19 DIM 27K CL	8	60	80	725	90.6	2700K	Clear	15,000	4.2	2.4	E26	3
8W A19 • Non-Dimmable													
LFF60A19N1527K	LED 60W EQ GLASS A19 ND 27K	8	60	80	725	90.6	2700K	Frosted	15,000	4.2	2.4	E26	3
LFF60A19N1550K	LED 60W EQ GLASS A19 ND 50K	8	60	80	725	90.6	5000K	Frosted	15,000	4.2	2.4	E26	3
LFC60A19N1527K	LED 60W EQ GLASS A19 ND 27K CL	8	60	80	725	90.6	2700K	Clear	15,000	4.2	2.4	E26	3
LFC60A19N1550K	LED 60W EQ GLASS A19 ND 50K CL	8	60	80	725	90.6	5000K	Clear	15,000	4.2	2.4	E26	3
LED All Glass Decorative 40W Equivalent • Dimmable • 15,000 Hour													
FG25D40V27W	LED 4W G25 DIM 27K FR Pro	4	40	80	350	87.5	2700K	Frosted	15,000	4.5	3.2	E26	3
FB11D40V27E12C	LED 4W B11 DIM 27K E12 CL PRO	4	40	80	350	87.5	2700K	Clear	15,000	3.5	1.4	E12	3
FB11D40V50E12C	LED 4W B11 DIM 50K E12 CL PRO	4	40	80	350	87.5	5000K	Clear	15,000	3.5	1.4	E12	3
LED A-LAMP • 15,000 Hour													
9W A19 • Dimmable													
L60A19D15V27K	LED 9W A19 DIM 2700K ProLine	9	60	80	800	88.9	2700K	Frosted	15,000	4.3	2.4	E26	3
9W A19 • Non-Dimmable													
L60A19N15V27K	LED 9W A19 ND 2700K ProLine	9	60	80	800	88.9	2700K	Frosted	15,000	4.3	2.4	E26	3
15W A19 • Dimmable													
L100A19D15V27K	LED 15W A19 DIM 2700K ProLine	15	100	80	1500	100.0	2700K	Frosted	15,000	4.5	2.6	E26	3
14W A19 • Non-Dimmable													
L100A19N15V27K	LED 14W A19 ND 2700K ProLine	14	100	80	1500	107.1	2700K	Frosted	15,000	4.5	2.6	E26	3
LED BR • Dimmable • 15,000 Hour													
L50R20D15V27K	LED 7W R20 DIM 2700K ProLine	7.5	50	80	500	66.7	2700K	Frosted	15,000	3.8	2.5	E26	3
L65BR30D15V27K	LED 9.5W BR30 DIM 2700K ProLine	9.5	65	80	650	68.4	2700K	Frosted	15,000	4.8	3.7	E26	3
L75BR40D15V27K	LED 14W BR40 DIM 2700K ProLine	14	75	80	1065	76.1	2700K	Frosted	15,000	5.6	7.3	E26	3
LED PAR* • Dimmable • 15,000 Hour													
L50P20D15V30KFL	LED 7W P20 DIM 30KFL ProLine	7	50	80	525	75	3000K	Frosted	15,000	3.4	2.3	E26	3
L75P30D15V30KFL	LED 10W P30 DIM 30KFL ProLine	9	75	80	720	80	3000K	Frosted	15,000	4.8	3.9	E26	3
L90P38D15V30KFL	LED 13W P38 DIM 30KFL ProLine	13	90	80	1100	84.6	3000K	Frosted	15,000	5.3	4.8	E26	3

* ALL PAR LAMPS HAVE A 40° BEAM ANGLE AND ARE SUITABLE FOR WET LOCATIONS.

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP JUN 2021/WF197107



3 YEAR WARRANTY
*Based on 12 hours use per day

TECHNOLOGY CAST IN A BEAUTIFUL LIGHT

For over 20 years, TCP has been designing, developing and delivering energy-efficient lighting into the market. Thanks to our cutting-edge technology and manufacturing expertise, we have shipped billions of high quality lighting products. With TCP, you can count on a lighting product that is designed to meet the needs of the market - that transforms your surroundings and envelopes you in warmth - lighting that generates beauty with every flip of the switch.

Sales:

Date:

Model:

Project:

Rep:

Catalog Number:

Type:

Notes:



For more information on the quality and care TCP can deliver, call us at **800.324.1496** or visit tcpi.com

325 Campus Dr. | Aurora, Ohio 44202 | P: 800.324.1496 | F: 877.487.0516