

DESCRIPTION

Reduce energy and maintenance costs by replacing 175W metal halide bulbs with these more efficient 45W LED corn bulbs.

FEATURES

- Delivers 155 LPW for highly efficient performance
- Mogul E39 base
- Ballasts, capacitors, and starters must be removed (bypassed) from fixture during installation; see installation instructions for more information

LISTINGS

- UL rated for damp locations
- Rated for use in enclosed fixtures
- FCC Part 15
- IP64
- CE
- RoHS
- DesignLights Consortium® 5.1 Standard - meets the requirements for the highest DLC qualification for efficacy and lumen maintenance; DLC PN - PLTBG421

PERFORMANCE

- CRI: >80
- CCT: 3000K
- LED L70 Life Hours: ≥100,000 hours
- Philips Lumileds LEDs

THERMAL

- -40°F to 113°F or (-40°C to 45°C) operating temperature

ELECTRICAL

- THD: <20%
- Power Factor: >0.9
- Input Voltage: 120-277V
- Surge Protection: 2kV

project name	type
catalog number	
comments	voltage
approved by	date



WARRANTY

- 5 year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Warehouses
- Security Lighting
- Parking Lot Lights
- Post Top Lights


PERFORMANCE	Power Consumption	45 Watt
	Bare Lamp Lumens	6975
	Bare Lamp Efficacy (LPW)	155
	Fixture Lumens*	5153
	Fixture Efficacy (LPW)*	119
	CRI	>80
	CCT	3000K
	LED L70 Life Hours	≥100,000
ELECTRICAL	Beam Angle	360 Degree
	Power Factor	<20%
	THD	>0.9
CONSTRUCTION	Input Voltage	120-277V
	Operating Temperature	-40°F to 113°F or (-40°C to 45°C)
LISTINGS	Base	E39
	Certifications	UL Listed; FCC; CE; IP64; DLC
	Material Usage	RoHS - No mercury or lead
	Environment	Enclosed Fixture Rated; Damp Location Rated

*Fixture lumens and efficacy based on testing in DLC approved fixture.

PERFORMANCE SUMMARY

Item #	Watts	Bare Lamp Lumens	Bare Lamp LPW	Voltage	Replaces	CCT	CRI	Beam	LED L70 Life Hours	DLC Level	DLC #
PLTS-12056	45	6975	155	120-277V	MH175	3000K	>80	360°	≥100,000	5.1 Standard	PLTBG421

DIMENSIONS



DIMENSIONS

Height: 9.57"

Width: 2.36"

Weight: 0.99 lbs

PHOTOMETRICS

