DesignLights Consortium





| Classification | Standard |
|------------------------|---|
| Primary Use | High-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 242.42 W |
| Reported Light Output | 31466.9 lm |
| Reported CCT | 4000 K |
| Product ID | PLDTOKAU291T |
| DLC Family Code | EMWAGB |
| Listing Status | Listed |
| Date Qualified | 2021-08-31 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting | |
|--------------------------------|---|--|
| Technical Requirements Version | 5.1 | |
| Product ID | PLDTOKAU291T | |
| Manufacturer | Precision Lighting & Transformer, Inc | |
| Brand | PLT | |
| Model Number | PLTSN1314[1;2;3]1[1;2;blank][1;blank]RP | |
| Parent | No | |
| Classification | Standard | |
| DLC Family Code | EMWAGB | |
| Input Power Type | AC | |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Indoor Luminaires | | |
|-------------------------|---|--|--|
| General Application | High-Bay | | |
| Primary Use Designation | High-Bay Luminaires for Commercial and Industrial Buildings | | |

PRODUCT CAPABILITIES VIEW DETAILS

| Integral Controls | Yes |
|------------------------------|------------------------------------|
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No Control Capability |

https://qpl.designlights.org/solid-state-lighting?search=PLTSN1314[1;2;3]1[1;2;blank][1;blank]RP

9/10/21, 8:13 AM

| Sensor Type | Occupancy Sensing |
|-------------------------------------|----------------------|
| Wired Communication Protocol | 0-10V Analog |
| Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | No |
| White-Tunable | No |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | Yes |
| Field Adjustable Distribution Type | Integral FALD |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 31466.9 lm |
|-------------------------------|-------------|
| Reported Efficacy (AC) | 129.81 lm/W |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 80 |
| Reported R9 | 20 |
| Reported IES Rf | 85 |
| Reported IES Rg | 97 |
| Reported IES Rcs,h1 | -10 |
| Reported Default Light Output | 31466.9 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 242.42 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15 % |
| Reported Power Factor | 0.9 |
| Reported Default Input Wattage | 240 |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Field Adjustable Light Distribution Setting | Pointing Straight Down |
|---|------------------------|
|---|------------------------|

VERSION HISTORY VIEW DETAILS

| 2021-08-31 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|
|------------|--------|-----|----------|