DesignLights Consortium





| Classification | Standard |
|------------------------|----------------------------------|
| Primary Use | Direct Linear Ambient Luminaires |
| Reported Input Wattage | 54 W |
| Reported Light Output | 6372 lm |
| Reported CCT | 3500 K |
| Reported CRI (Ra) | 82 |
| Product ID | PR4U6KCO |
| DLC Family Code | EEEGKI |
| Listing Status | Listed |
| Date Qualified | 2021-09-03 |

PRODUCT INFORMATION VIEW DETAILS

| Solid State Lighting |
|---------------------------------------|
| 5.1 |
| PR4U6KCO |
| Precision Lighting & Transformer, Inc |
| PLT |
| PLTM445142 |
| Yes |
| Standard |
| EEEGKI |
| 4 ft |
| AC |
| |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Indoor Luminaires |
|-------------------------|----------------------------------|
| General Application | Linear Ambient |
| Primary Use Designation | Direct Linear Ambient Luminaires |

PRODUCT CAPABILITIES VIEW DETAILS

| Integral Controls | No |
|-------------------------------------|------------------------------------|
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No Control Capability |
| Sensor Type | No Sensor |
| Wired Communication Protocol | 0-10V Analog |
| Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | TRUE |
| White-Tunable | Yes |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | No |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 6372 lm |
|-------------------------------|----------|
| Reported Efficacy (AC) | 118 lm/W |
| Reported CCT | 3500 K |
| Reported CRI (Ra) | 82 |
| Reported R9 | 14 |
| Reported IES Rf | 80 |
| Reported IES Rg | 90 |
| Reported IES Rcs,h1 | -12 |
| Reported Default Light Output | 6372 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 54 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 10 % |
| Reported Power Factor | 0.9 |
| Reported Minimum Input Wattage | 34 |
| Reported Maximum Input Wattage | 54 |
| Reported Default Input Wattage | 54 |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Tested Light Output | 6395.92 lm |
|----------------------|-------------|
| Tested Efficacy (AC) | 119.44 lm/W |
| Tested CCT | 3553 K |
| Tested CRI (Ra) | 84 |
| | |

| Tested R9 | 13 |
|-------------------|---------|
| Tested IES Rf | 84 |
| Tested IES Rg | 94 |
| Tested IES Rcs,h1 | -12 % |
| Tested Duv | -0.0017 |

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Tested Voltage | 120 |
|----------------------------------|---------|
| Tested Input Wattage | 53.55 W |
| Tested Total Harmonic Distortion | 16.55 % |
| Tested Power Factor | 0.9178 |

VERSION HISTORY VIEW DETAILS