

Exit & Emergency

Evade Exit/Emergency Combination Series

- LED Life-Cycle exceeding 10 years
- Red & Green Face
- Dual Voltage 120 or 277 VAC Input
- Remote Capability Option
- Fully Rotatable Heads
- Single & Double Face Configurations

Specifications

Description

The Evade Series Exit and Emergency Combo Family offers a quality exit and emergency lighting solution for hallway, stairwell and other Life Safety applications. The low profile design makes it ideal to mount on walls or ceilings indicating and illuminating the path of egress for a minimum of 90 minutes after a power loss.

Electrical

- 120 or 277 VAC Input
- Test Emergency Button and Battery Charging Indicator
- Long-Life Maintenance Free NiCad Battery
- 24 Hour Recharge Time
- Battery Low Voltage Protection Circuit
- .75W Lamp Heads Delivering 150 Total Lumens at CCT of 5700K

Certifications

- UL924
- NFPA 101 and NFPA 70
- CEC T20 Compliant
- Damp Location Listed



Construction & Mounting

- Injection-Molded Thermoplastic Housing with 5VA Flame Retardant
- Exit Lettering 6" height and 3/4" Stroke
- Snap In and Out Chevrons
- Suitable for Wall and Ceiling Mount
- Universal J-Box Mounting Pattern on Back Plate

Evade Exit/Emergency Combination Series

Ordering Information

Product SKU	Product Code	Product Description
95004	EV-EXC-GR	Evade Exit Sign & Emergency Combination Unit with Green Lettering
95005	EV-EXC-RD	Evade Exit Sign & Emergency Combination Unit with Red Lettering
95006	EV-EXC-GR-RC	Evade Exit Sign & Emergency Combination Unit with Green Lettering and Remote Capability
95007	EV-EXC-RD-RC	Evade Exit Sign & Emergency Combination Unit with Red Lettering and Remote Capability
Remote Heads		
95010	EV-RH-1-IND	Evade Single Remote Indoor Head
95011	EV-RH-2-IND	Evade Dual Remote Indoor Head
95012	EV-RH-1-OUT	Evade Single Remote Outdoor Head
95013	EV-RH-2-OUT	Evade Double Remote Outdoor Head

Specifications Table

	EV-EXC-GR	EV-EXE-RD	EV-EXE-GR-RC	EV-EXE-RD-RC
Letter Color	Green	Red	80mA Max	100mA Max
Input	30mA Max		33mA Max	
Wattage	2.8W		3.5W	
Battery	Ni-cad 3.6V900mAh		Ni-cad 3.6V900mAh (2)	
Lamp Head Wattage	.75W Ea (1.5W Total)			
Lamp Head Lumens	150 LM			
Recharge Time	24 Hours			
Voltage	120 or 277 VAC			
Frequency	60Hz			
Housing	Injection-Molded Thermoplastic Housing			
Testing Function	Manual Push to Test Button			
Operating Temperature	10°C to 40°C			
Listings & Compliance	UL 924, CEC Title 20, NFPA 70 & NFPA 101			
Environment	Damp Location Listed			
Warranty	2 Year Battery			

Evade Exit/Emergency Combination Series

Remote Head Specifications

Product SKU	Product Code	Input Voltage	Input Wattage	Lumens
95010	EV-RH-1-IND	3.6VDC	.75W	85
95011	EV-RH-2-IND	3.6VDC	1.5W	170
95012	EV-RH-1-OUT	3-12VDC	.75W	90
95013	EV-RH-2-OUT	3-12VDC	1.5W	180

Remote Head

EV-RH-IND

- Single Remote Indoor Head
- Suitable for Damp Location. UL, cUL Listed



EV-RH-2 IND

- Dual Remote Indoor Head
- Suitable for Damp Location. UL, cUL Listed



EV-RH-1-OUT

- Single Remote Outdoor Head
- Suitable for Wet Location. UL, cUL Listed



EV-RH-2-OUT

- Dual Remote Outdoor Heads
- Suitable for Wet Location. UL, cUL Listed



Dimensions

