

Exit & Emergency

Evade Series Emergency Light

- LED Life-Cycle exceeding 10 years
- Wall or Ceiling Mount
- Dual Voltage 120 or 277 VAC Input
- Remote Capability Option
- Fully Rotatable Heads

Specifications

Description

The Evade Series Emergency Light offers a quality emergency lighting solution for hallway, stairwells and other Life Safety applications. The compact design makes it ideal to mount on walls or ceilings, illuminating the path of egress for a minimum of 90 minutes after a power loss.

Electrical

- 120 or 277 VAC Input
- Test Emergency Button and Battery Charging Indicator
- Long-Life Maintenance Free NiCad Battery
- 24 Hour Recharge Time

Certifications

- UL924
- NFPA 101 and NFPA 70
- CEC T20 Compliant
- Damp Location Listed



Construction & Mounting

- Injection-Molded Thermoplastic Housing with 5VA Flame Retardant
- Installer Friendly Configuration Design for Quick Install
- Suitable for Wall and Ceiling Mounts
- Universal J-Box Mounting Pattern on Back Plate

Evade Series Emergency Light

Ordering Information

Product SKU	Product Code	Product Description
95008	EV-EME-R	Evade Emergency Unit
95009	EV-EME-R-RC	Evade Emergency with Remote Capability
Remote Heads		
95010	EV-RH-1-IND	Evade Single Remote Indoor Head
95011	EV-RH-2-IND	Evade Dual Remote Indoor Head
95012	EV-RH-1-OUT	Evade Single Remote Outdoor Head
95013	EV-RH-2-OUT	Evade Double Remote Outdoor Head

Specifications Table

	EV-EME-R	EV-EME-R-RC
Input Current	80mA Max	100mA Max
Input Wattage	0.8W	1W
Battery	Ni-Cad	Ni-Cad
Lamp Head Wattage	1W Ea (2W Total)	
Lamp Head Lumens	240 LM	220 LM
Recharge Time	24 Hours	
Voltage	120 or 277 VAC	
Frequency	60Hz	
Housing	Injection-Molded Thermoplastic Housing	
Testing Function	Manual Push to Test Button	
Operating Temperature	10°C to 40°C	
Listings & Compliance	UL 924, CEC Title 20, NFPA 70 & NFPA 101	
Environment	Damp Location Listed	
Warranty	2 Year Battery	

Evade Series Emergency Light

Remote Head Specifications

Product SKU	Product Code	Input Voltage	Input Wattage	Lumens
95010	EV-RH-1-IND	3.6VDC	.75W	85
95011	EV-RH-2-IND	3.6VDC	1.5W	170
95012	EV-RH-1-OUT	3-12VDC	.75W	90
95013	EV-RH-2-OUT	3-12VDC	1.5W	180

Remote Head

EV-RH-1-IND

- Single Remote Indoor Head
- Suitable for Damp Location. UL, cUL Listed



EV-RH-2-IND

- Double Remote Indoor Head
- Suitable for Damp Location. UL, cUL Listed



EV-RH-1-OUT

- Single Remote Outdoor Head
- Suitable for Wet Location. UL, cUL Listed



EV-RH-2-OUT

- Dual Remote Outdoor Heads
- Suitable for Wet Location. UL, cUL Listed



Dimensions

