

Installation Instruction

A0

Cautions:

1. Do not use an electric generator to test this fixture
2. Please abide by related country, regional and local law and regulations when installing this fixture.
3. Please turn off the power before installation or maintenance.
4. Proper earth grounding is required to ensure safety.

Notice:


1. To avoid the possibility of electrical shock or fire, the installation personnel must have professional electric knowledge.
2. Please wear gloves to avoid injury before installation.
3. If any smoke or spark of wire occurs, please turn off the power immediately and notify relevant personnel.
4. Please use a listed water proof strain relief bushing when connecting the supply cord to the outlet box.

Attention:

1. Please check if there is any damage during shipping. If so, please contact manufacturer at once.
2. Please read the installation instruction carefully to check whether all the accessories are complete. After confirmation, then install the fixture according to installation steps.

Wiring Diagram & Instruction:

This led high bay light is available with 0-10V dimming.



Notice:
As for the wire color of DIM+, DIM- and AUX+, please check the fixture wire label.

Ring Mount Installation

1. Screw the ring into the fixture and tighten it securely. (figure 1)
2. Hang the fixture on the ceiling hook or chain. (figure 2)
3. After installation, connect the fixture wiring to the AC mains (including dimming wiring if desired) in accordance with applicable electrical regulations ensuring all connections are stable and well protected.



Figure 1




Figure 2

Description:

This product is 0-10V dimmable, the below dimmers are recommended:

Brand	Model
LUTRON	NTSTV-DV
LEVITON	DS710-10Z/IP710
LEGRAND	RH4FBL3PW

Installation for PC Reflector

1. Lock the PC reflector to the fixture with screws
2. Installation complete

