

DESCRIPTION

Greatly reduce your energy costs by replacing colored halogen bulbs in your recessed and track lighting with these more efficient and longer lasting red LED MR16 bulbs.

FEATURES

- Efficiently replaces a 35W halogen bulb
- Produces a 30-degree flood beam angle ideal for ambient lighting
- GX5.3 base

LISTINGS

- CE rated for indoor/dry locations
- RoHS

WARRANTY

- 1 year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Track Lighting
- Downlights

| | |
|----------------|---------|
| project name | type |
| catalog number | |
| comments | voltage |
| approved by | date |



| | | |
|---------------------|-------------------|---------------------------|
| PERFORMANCE | Power Consumption | 4 Watt |
| | Lumens | 350 |
| | Efficacy (LPW) | 88 |
| | Beam Angle | 30 degree |
| | CCT | Red |
| ELECTRICAL | Life (L70) | 50000 |
| | Input Voltage | 12V |
| CONSTRUCTION | Shape | MR16 |
| | Base | GX5.3 |
| LISTINGS | Certifications | CE Rated |
| | Material Usage | RoHS – No mercury or lead |
| | Environment | Indoor/Dry Location Rated |

PERFORMANCE SUMMARY

| Item # | Shape | Lumens | Wattage | LPW | Voltage | Replaces | CCT | Life/Hours | Dimmable |
|------------|-------|--------|---------|-----|---------|-------------|-----|------------|----------|
| PLTS-30112 | MR16 | 350 | 4 | 88 | 12V | 35W Halogen | Red | 50,000 | No |

DIMENSIONS



DIMENSIONS

Height: 2.0"

Diameter: 1.95"

WARNINGS

- Not for use with dimmers.
- Not rated for use in enclosed fixtures.