

# DesignLights Consortium



Classification	Standard
Primary Use	Dual Mode Internal Driver (UL Type A and Type B)
Reported Input Wattage	27.5 W
Reported Light Output	3300 lm
Reported CCT	5000 K
Reported CRI (Ra)	83
Product ID	P2SFRTQ9
DLC Family Code	<a href="#">ZZZFDX</a>
Listing Status	Listed
Date Qualified	2021-12-01

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	P2SFRTQ9
Manufacturer	IRTRONIX INC DBA EURI LIGHTING
Brand	EURI LIGHTING
Model Number	ET5-24W305H
Parent	No
Classification	Standard
DLC Family Code	ZZZFDX
Length	4.0 ft
Input Power Type	AC
Notes	Dimmable depending on ballast capability. Dimmable depending on ballast capability

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp
General Application	T5HO Four-Foot
Primary Use Designation	Dual Mode Internal Driver (UL Type A and Type B)

## PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
Wired Communication Protocol	0-10V Analog
Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	180 °
Reported Light Output	3300 lm
Reported Efficacy (AC)	120 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	83
Reported R9	10
Reported IES Rf	84
Reported IES Rg	97
Reported IES Rcs,h1	-11
Reported Default Light Output	3300 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	27.5 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.9
Reported Default Input Wattage	27.5
Voltage Range	120-277 V

## VERSION HISTORY VIEW DETAILS

2021-12-01	Listed	5.1	Standard
------------	--------	-----	----------