

DesignLights Consortium



Classification	Standard
Primary Use	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	40 W
Reported Light Output	4400 lm
Reported CCT	3500 K
Reported CRI (Ra)	82
Product ID	PLRICZ3NQP28
DLC Family Code	MMMSLQ
Listing Status	Listed
Date Qualified	2020-05-28

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLRICZ3NQP28
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM51111
Parent	Yes
Classification	Standard
DLC Family Code	MMMSLQ
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	1x4 Luminaires for Ambient Lighting of Interior Commercial Spaces

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
Wired Communication Protocol	0-10V Analog
Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4400 lm
Reported Efficacy (AC)	110 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82
Reported R9	2
Reported IES Rf	80
Reported IES Rg	90
Reported IES Rcs,h1	-12
Reported Minimum Light Output	2900 lm
Reported Maximum Light Output	4400 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	4400 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	40 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	25
Reported Maximum Input Wattage	40
Reported Default Input Wattage	40
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	4407 lm
Tested Efficacy (AC)	110.92 lm/W
Tested CCT	3357 K

Tested CRI (Ra)	82
Tested R9	2
Tested IES Rf	83
Tested IES Rg	97
Tested IES Rcs,h1	-12 %
Tested Duv	0.0005

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	40 W
Tested Total Harmonic Distortion	12 %
Tested Power Factor	0.958
Tested Maximum Input Wattage	39.7 W

VERSION HISTORY VIEW DETAILS

2020-05-28	Listed	5	Standard
------------	--------	---	----------