

DesignLights Consortium



Classification	Standard
Primary Use	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	40 W
Reported Light Output	4400 lm
Reported CCT	3500 K
Reported CRI (Ra)	82
Product ID	PLZ1TAZ9WJP3
DLC Family Code	MMMSLR
Listing Status	Listed
Date Qualified	2020-05-28

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLZ1TAZ9WJP3
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM52111
Parent	Yes
Classification	Standard
DLC Family Code	MMMSLR
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
Wired Communication Protocol	0-10V Analog
Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4400 lm
Reported Efficacy (AC)	110 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82
Reported R9	2
Reported IES Rf	80
Reported IES Rg	90
Reported IES Rcs,h1	-12
Reported Minimum Light Output	2900 lm
Reported Maximum Light Output	4400 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	4400 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	40 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	25
Reported Maximum Input Wattage	40
Reported Default Input Wattage	40
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	4396 lm
Tested Efficacy (AC)	109.9 lm/W
Tested CCT	3408 K

Tested CRI (Ra)	81
Tested IES Rf	83
Tested IES Rg	97
Tested IES Rcs,h1	-13 %
Tested Duv	0.0003

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	40 W
Tested Total Harmonic Distortion	11 %
Tested Power Factor	0.986
Tested Maximum Input Wattage	40 W

VERSION HISTORY VIEW DETAILS

2020-05-28	Listed	5	Standard
------------	--------	---	----------