DesignLights Consortium





| Classification | Standard |
|------------------------|---|
| Primary Use | Replacement Lamps (plug and play) (UL Type A) |
| Reported Input Wattage | 28 W |
| Reported Light Output | 3500 lm |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 82 |
| Product ID | PLYFOI8HSOKZ |
| DLC Family Code | IIINFD |
| Listing Status | Listed |
| Date Qualified | 2019-05-22 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting | |
|--------------------------------|---------------------------------------|--|
| Technical Requirements Version | 5.1 | |
| Product ID | PLYFOI8HSOKZ | |
| Manufacturer | Precision Lighting & Transformer, Inc | |
| Brand | PLT | |
| Model Number | PLTSP56114 | |
| Parent | No | |
| Classification | Standard | |
| DLC Family Code | IIINFD | |
| Length | 4.0 ft | |
| Input Power Type | AC | |
| Notes | Updated on 10/25/2021 | |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Linear Replacement Lamp | |
|---|-------------------------|--|
| General Application | T5HO Four-Foot | |
| Primary Use Designation Replacement Lamps (plug and play) (UL Type A) | | |

PRODUCT CAPABILITIES VIEW DETAILS

| Integral Controls | No | | |
|-------------------------------------|------------------------------------|--|--|
| Dimming Capability and Range | Continuous Dimming to 10% or below | | |
| Integral Control Capability | No Control Capability | | |
| Sensor Type | No Sensor | | |
| Wired Communication Protocol | 0-10V Analog | | |
| Wireless Communication Protocol | No Wireless Protocol | | |
| Field Adjustable Light Output | No | | |
| White-Tunable | No | | |
| Warm-Dimming | No | | |
| Field Adjustable Light Distribution | No | | |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Beam Angle | 180 ° |
|-------------------------------|----------|
| Reported Light Output | 3500 lm |
| Reported Efficacy (AC) | 125 lm/W |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 82 |
| Reported R9 | 0 |
| Reported IES Rf | 81 |
| Reported IES Rg | 94 |
| Reported IES Rcs,h1 | -13 |
| Reported Default Light Output | 3500 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 28 W |
|------------------------------------|------|
| Reported Total Harmonic Distortion | 20 % |
| Reported Power Factor | 0.9 |
| Reported Default Input Wattage | 28 |

VERSION HISTORY VIEW DETAILS

| 2021-10-26 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|
| 2020-03-30 | Listed | 5 | Standard |
| 2019-05-22 | Listed | 4.4 | Standard |