# **DesignLights Consortium**





Classification	Standard		
Primary Use	Dual Mode Internal Driver (UL Type A and Type B)		
Reported Input Wattage	15 W		
Reported Light Output	1800 lm		
Reported CCT	3500 K		
Reported CRI (Ra)	82		
Product ID	PL0037CSE2ME		
DLC Family Code	SSSDZN		
Listing Status	Listed		
Date Qualified	2020-10-30		

#### PRODUCT INFORMATION VIEW DETAILS

Solid State Lighting		
5.1		
PL0037CSE2ME		
Precision Lighting & Transformer, Inc		
PLT		
PLTSP3B313		
No		
Standard		
SSSDZN		
4.0 ft		
AC		
Updated on 10/25/2021		

### PRODUCT CATEGORIZATION VIEW DETAILS

Category Linear Replacement Lamp	
General Application	T8 Four-Foot
Primary Use Designation	Dual Mode Internal Driver (UL Type A and Type B)

#### PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No		
Dimming Capability and Range	Continuous Dimming to 10% or below		
Integral Control Capability	No Control Capability		
Sensor Type	No Sensor		
Wired Communication Protocol	0-10V Analog		
Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	No		
White-Tunable	No		
Warm-Dimming	No		
Field Adjustable Light Distribution	No		

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	210 °
Reported Light Output	1800 lm
Reported Efficacy (AC)	120 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82
Reported R9	7
Reported IES Rf	81
Reported IES Rg	94
Reported IES Rcs,h1	-13
Reported Default Light Output	1800 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	15 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	15
Voltage Range	120-277 V

## **VERSION HISTORY VIEW DETAILS**

2021-10-26	Listed	5.1	Standard
2020-10-30	Listed	5	Standard