

# DesignLights Consortium



Classification	Standard
Primary Use	Architectural Flood and Spot Luminaires
Reported Input Wattage	15 W
Reported Light Output	1650 lm
Reported CCT	5000 K
Reported CRI (Ra)	80
Product ID	P0YKFOLS
DLC Family Code	<a href="#">HHHDOR</a>
Listing Status	Listed
Date Qualified	2020-04-21

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.0
Product ID	P0YKFOLS
Manufacturer	Technical Consumer Products
Brand	TCP
Model Number	FLYUA1W50KBR
Parent	No
Classification	Standard
DLC Family Code	HHHDOR
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Low Output
Primary Use Designation	Architectural Flood and Spot Luminaires

## PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No
-------------------	----

Dimming Capability and Range	Continuous Dimming to 10% or below
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	1650 lm
Reported Efficacy (AC)	110 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	80
Reported Default Light Output	1650 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	15 W
Reported Total Harmonic Distortion	22 %
Reported Power Factor	0.9
Reported Maximum Input Wattage	15
Reported Default Input Wattage	15
Voltage Range	120-277 V

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Field Adjustable Light Distribution Setting	straight down
---	---------------

## VERSION HISTORY VIEW DETAILS

2021-02-28	Listed	5	Standard
2020-04-21	Listed	4.4	Premium