

DESCRIPTION

Easily schedule security and holiday lighting with this plug-in outdoor digital timer with photocell and remote.

FEATURES

- Can be operated with included remote or with buttons on the timer
- Remote must be within 100 ft. of timer in order to operate it
- Photocell allows for dusk-till-dawn operation; timer can be set to remain on for 2, 4, 6, or 8 hours
- Has 2 outlets
- Comes with 0.5 ft. SJTW 14AWG/3C 3-prong power cord

LISTINGS

- UL rated for indoor and outdoor use
- FCC Part 15

THERMAL

- -40°F to 40°F or (-40°C to 104°C) operating temperature

ELECTRICAL

- Voltage: 125V
- Amperage: 15A

WARRANTY

- 1 year prorated warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Security Lighting
- Holiday Lights

project name	type
catalog number	
comments	voltage
approved by	date



PERFORMANCE	Maximum Wattage	1000W
	Maximum Amperage	15A
	Sensor Type	Photocell
ELECTRICAL	Input Voltage	125V
	HP Rating	1/2 HP
	Wire Gauge	14 AWG
OUTLETS	NEMA	5-15R
	# of Outlets	2
REMOTE	Battery	3V (CR2032)
CONSTRUCTION	Operating Temperature	-40°F to 40°F or (-40°C to 104°C)
	Housing	Plastic
	Finish	Black
LISTINGS	Certifications	UL Listed, FCC
	Environment	Indoor/Outdoor Rated

PERFORMANCE SUMMARY

Item #	Max. Wattage	Max. Amperage	Voltage	HP Rating	# of Outlets	Remote Capable	Timer	Sensor Type	Finish
PLTS-12337	1000W	15A	125V	1/2 HP	2	Yes	Digital	Photocell	Black

DIMENSIONS



DIMENSIONS

Length: 4.2"
Width: 2.8"
Depth: 1.7"
Power Cord Length: 0.5'



REMOTE CONTROL

Length: 3.1"
Width: 1.6"
Depth: 0.7"

WARNINGS

- Do not submerge in water.
- Timer is raintight only when mounted vertically with the receptacle facing downward and mounted at least 2 ft. above the ground.