



DESCRIPTION

Provide power and set on & off times to holiday lighting with these outdoor power outlet yard stakes with built-in photocell and digital timer.

FEATURES

- Can be operated with RF remote (included) or with buttons on the stake
- Remote must be within 100 ft. of yard stake in order to control it
- Photocell allows for dusk-till-dawn operation
- 2, 4, 6, or 8-hour on/off settings; see installation instructions for more information
- Outlets are protected with water-proof covers
- Comes with 6 ft. SJTW 14AWG/3C 3-prong power cord
- Installs with included plastic yard stake

LISTINGS

- UL rated for indoor and outdoor use
- FCC Part 15

ELECTRICAL

- Voltage: 125V
- Amperage: 13A, 15A

WARRANTY

- 1 year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Warehouses
- Security Lighting
- Post Top Lights

project name	type
catalog number	
comments	voltage
approved by	date



PERFORMANCE	Maximum Wattage	1625W, 1875W
	Maximum Amperage	13A, 15A
ELECTRICAL	Input Voltage	125V
	Wire Gauge	14 AWG
OUTLETS	NEMA	5-15R
	# of Outlets	3, 6
REMOTE	Battery	3V (CR2032)
CONSTRUCTION	Housing	Plastic
	Finish	Garden Green
LISTINGS	Certifications	UL Listed, FCC
	Environment	Indoor/Outdoor Rated

PERFORMANCE SUMMARY

Item #	Max. Wattage	Max. Amperage	Voltage	# of Outlets	Remote Capable	Timer	Photocell	Finish
PLTS-12332	1875W	15A	125V	6	Yes	Digital	Yes	Garden Green
PLTS-12333	1625W	13A	125V	3	Yes	Digital	Yes	Garden Green

DIMENSIONS

1875W POWER STAKE

BODY

Length: 8.75"

Width: 3.5"

Depth: 3"

YARD STAKE

Length: 12.5"

Width: 1.5"

REMOTE CONTROL

Length: 3.25"

Width: 1.5"

Depth: 0.63"



1625W POWER STAKE

BODY

Length: 8.5"

Width: 3.5"

Depth: 2.8"

YARD STAKE

Length: 12.5"

Width: 1.5"

REMOTE CONTROL

Length: 3.1"

Width: 1.5"

Depth: 0.8"



WARNINGS

- For temporary use. Do not exceed 90 days.
- If amperage of lighting is unknown, do not connect more than 140 screw-base lamps (C7 or C9) or 12 mini light strings to this power stake.
- Connector must be at least 6 inches above the ground.
- Do not use outdoors if temperatures drop below -40°F (-40°C)