

DesignLights Consortium



| | |
|------------------------|--|
| Classification | Standard |
| Primary Use | Dual Mode Internal Driver (UL Type A and Type B) |
| Reported Input Wattage | 16.5 W |
| Reported Light Output | 1980 lm |
| Reported CCT | 5000 K |
| Reported CRI (Ra) | 83 |
| Product ID | S-XW5DFR |
| DLC Family Code | YYYYFGE |
| Listing Status | Listed |
| Date Qualified | 2022-05-13 |

PRODUCT INFORMATION VIEW DETAILS

| | |
|--------------------------------|--|
| Qualified Product List | Solid State Lighting |
| Technical Requirements Version | 5.1 |
| Product ID | S-XW5DFR |
| Manufacturer | Precision Lighting & Transformer, Inc |
| Brand | PLT |
| Model Number | PLTP1235 |
| Parent | No |
| Classification | Standard |
| DLC Family Code | YYYYFGE |
| Input Power Type | AC |
| Notes | Dimmable depending on ballast capability. Dimmable depending on ballast capability |

PRODUCT CATEGORIZATION VIEW DETAILS

| | |
|-------------------------|--|
| Category | Linear Replacement Lamp |
| General Application | U-Bend Replacement Lamps |
| Primary Use Designation | Dual Mode Internal Driver (UL Type A and Type B) |

PRODUCT CAPABILITIES VIEW DETAILS

| | |
|-------------------|----|
| Integral Controls | No |
|-------------------|----|

| | |
|--|------------------------------------|
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No Control Capability |
| Sensor Type | No Sensor |
| SSL V5 Wired Communication Protocol | No Wired Communication Protocol |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | No |
| White-Tunable | No |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | No |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|-------------------------------|----------|
| Reported Beam Angle | 160 ° |
| Reported Light Output | 1980 lm |
| Reported Efficacy (AC) | 120 lm/W |
| Reported CCT | 5000 K |
| Reported CRI (Ra) | 83 |
| Reported R9 | 10 |
| Reported IES Rf | 85 |
| Reported IES Rg | 97 |
| Reported IES Rcs,h1 | -11 |
| Reported Default Light Output | 1980 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| | |
|------------------------------------|-----------|
| Reported Input Wattage | 16.5 W |
| Reported Total Harmonic Distortion | 10 % |
| Reported Power Factor | 0.9 |
| Reported Default Input Wattage | 16.5 |
| Voltage Range | 120-277 V |

VERSION HISTORY VIEW DETAILS

| | | | |
|------------|--------|-----|----------|
| 2022-05-13 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|