



Product Number: 21110
Order Abbreviation: CF18DD/835/ECO
General Description: DULUX 18W double compact fluorescent lamp with 2-pin base, 3500K color temperature, 82 CRI, ECOLOGIC for use on magnetic ballast

Product Information	
Abbrev. With Packaging Info.	CF18DD835ECO 50/CS 1/SKU
Average Rated Life (hr)	10000
Base	G24D-2
Bulb	D (T4)
Color Rendering Index (CRI)	82
Color Temperature/CCT (K)	3500
Family Brand Name	Dulux® D
Industry Standards	ANSI C78.901 - 2001, IEC 60901- 0518
Mean Lumens at 25C	989
Maximum Overall Length - MOL (in)	6.0
Maximum Overall Length - MOL (mm)	153
Nominal Wattage (W)	18.00

Additional Product Information
<u>Product Documents, Graphs, and Images</u>
<u>Packaging Information</u>

Footnotes
<ul style="list-style-type: none"> ● Approximate initial lumens after 100 hours operation. ● 2 pin CF lamps are not suitable for use in frequently cycled applications or with occupancy sensors. 2 pin CF lamps should never be installed in 4 pin sockets regardless if lamp will fit. ● SYLVANIA ECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local & state regulations. For more information, please visit www.lamprecycle.org
<ul style="list-style-type: none"> ● 2 pin CF lamps should never be installed in 4 pin sockets regardless if lamp will fit. ● The life ratings of fluorescent lamps are based on 3 hr. burning cycles under specified conditions and with ballast meeting ANSI specifications. If burning cycle is increased, there will be a corresponding increase in the average hours life. ● Rule of Thumb for Compact Fluorescent Lamps: Divide wattage of incandescent lamp by 4 to determine approximate wattage of compact fluorescent lamp that will provide similar light output. ● Minimum starting temperature: CF5: -22 degrees F; CF7: -4 degrees F; CF9: 14 degrees F; CF13DS: 14 degrees F; CF13DD: -4 degrees F; CF18DD: 5 degrees F; CF18DT: -4 degrees F; CF26: 14 degrees F.

