



**ProLume.**  
◀ Plug-Ins

COMPACTS

## ProLume® Plug-Ins



### Energy Efficient

- Save up to 80% in energy costs compared to standard incandescent lamps
- Tri-phosphor coating enhances lumen efficacy and color rendering, 82 CRI

### Technical Data

- Operating temperature 0 - 140°F
- Lead-free glass
- End-of-Life protection

### Broad Assortment

- Single and Double Tube 2-Pin
- Single, Double, Triple and Spiral Tube 4-Pin
- Flat Quad 4-Pin
- 2700, 3500, 4100 and 5000K

### Long Life


- 10,000 Hours Average Rated Life
- 1-Year Guarantee

### Benefits

- Saves energy
- Low maintenance
- Excellent color rendering
- TCLP compliant

### Applications

- Wall sconces
- Down lighting
- Task lighting
- Security

The **Eco-Shield®**  mark indicates this product is TCLP compliant.

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at [halcolighting.com](http://halcolighting.com).

Your account representative is your single source for pricing, orders, and technical support.

Shipping from Atlanta, Cleveland, Houston, and Phoenix.

ISO 9001 Certified




**where there's light,  
there's halco®**

(800) 677-3334

[halcolighting.com](http://halcolighting.com)

Bulb Type	Watts	Base	Item #	Product Code	Description	Pkg/Qty	Color Temp	CRI	Initial Lumens	Avg Rated Life	MOL (Inches)
<b>SINGLE TUBE 2-PIN</b>											
T4	5	G-23	109100	PL5S/27	Warm White EOL	1/50	2700	82	250	10000	4.3"
T4	5	G-23	109102	PL5S/41	Cool White EOL	1/50	4100	82	250	10000	4.3"
T4	7	G-23	109106	PL7S/27	Warm White EOL	1/50	2700	82	400	10000	5.4"
T4	7	G-23	109107	PL7S/35	White EOL	1/50	3500	82	400	10000	5.4"
T4	7	G-23	109108	PL7S/41	Cool White EOL	1/50	4100	82	400	10000	5.4"
T4	9	G-23	109112	PL9S/27	Warm White EOL	1/50	2700	82	600	10000	6.6"
T4	9	G-23	109144	PL9S/35	White EOL	1/50	3500	82	600	10000	6.6"
T4	9	G-23	109116	PL9S/41	Cool White EOL	1/50	4100	82	600	10000	6.6"
T4	9	G-23	109118	PL9S/50	Natural White EOL	1/50	5000	82	600	10000	6.6"
T4	13	GX23	109126	PL13S/27	Warm White EOL Eco-Shield®	1/50	2700	82	825	10000	7.2"
T4	13	GX23	109128	PL13S/35	White EOL Eco-Shield®	1/50	3500	82	825	10000	7.2"
T4	13	GX23	109130	PL13S/41	Cool White EOL Eco-Shield®	1/50	4100	82	825	10000	7.2"
T4	13	GX23	109132	PL13S/50	Natural White EOL Eco-Shield®	1/50	5000	82	825	10000	7.2"
<b>DOUBLE TUBE 2-PIN</b>											
T4	9	G23-2	109110	PL9D/27	Warm White EOL	1/50	2700	82	525	10000	4.3"
T4	9	G23-2	109120	PL9D/41	Cool White EOL	1/50	4100	82	525	10000	4.3"
T4	13	GX23-2	109146	PL13D/27	Warm White EOL Eco-Shield®	1/50	2700	82	900	10000	4.7"
T4	13	GX23-2	109148	PL13D/35	White EOL Eco-Shield®	1/50	3500	82	900	10000	4.7"
T4	13	GX23-2	109150	PL13D/41	Cool White EOL Eco-Shield®	1/50	4100	82	900	10000	4.7"
T4	13	GX23-2	109149	PL13D/50	Natural White EOL Eco-Shield®	1/50	5000	82	900	10000	4.7"
T4	18	G24d-2	109152	PL18D/27	Warm White EOL	1/50	2700	82	1200	10000	6.0"
T4	18	G24d-2	109154	PL18D/35	White EOL	1/50	3500	82	1200	10000	6.0"
T4	18	G24d-2	109156	PL18D/41	Cool White EOL	1/50	4100	82	1200	10000	6.0"
T4	18	G24d-2	109159	PL18D/50	Natural White EOL	1/50	5000	82	1200	10000	6.0"
T5	22	GX32d-2	109862	PL22D/27	Warm White	1/50	2700	82	1200	10000	6.1"
T5	22	GX32d-2	109864	PL22D/50	Natural White	1/50	5000	82	1200	10000	6.1"
T4	26	G24d-3	109158	PL26D/27	Warm White EOL Eco-Shield®	1/50	2700	82	1800	10000	6.8"
T4	26	G24d-3	109160	PL26D/35	White EOL Eco-Shield®	1/50	3500	82	1800	10000	6.8"
T4	26	G24d-3	109162	PL26D/41	Cool White EOL Eco-Shield®	1/50	4100	82	1800	10000	6.8"
T4	26	G24d-3	109163	PL26D/50	Natural White EOL Eco-Shield®	1/50	5000	82	1800	10000	6.8"
T5	28	GX32d-3	109870	PL28D/28	Warm White	10/50	2800	82	1600	10000	6.7"
T5	28	GX32d-3	109868	PL28D/50	Natural White	10/50	5000	82	1600	10000	6.7"
<b>SINGLE TUBE 4-PIN ELECTRONIC</b>											
T4	13	2GX7	109134	PL13S/E/27	Warm White EOL	1/50	2700	82	825	10000	6.7"
T4	13	2GX7	109136	PL13S/E/35	White EOL	1/50	3500	82	825	10000	6.7"
T4	13	2GX7	109138	PL13S/E/41	Cool White EOL	1/50	4100	82	825	10000	6.7"
T4	13	2GX7	109140	PL13S/E/50	Natural White EOL	1/50	5000	82	825	10000	6.7"
<b>DOUBLE TUBE 4-PIN ELECTRONIC</b>											
T4	13	G24q-1	109037	PL13D/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	900	10000	5.2"
T4	13	G24q-1	109035	PL13D/E/30	Soft White EOL Eco-Shield®	1/50	3000	83	900	10000	5.2"
T4	13	G24q-1	109038	PL13D/E/35	White EOL Eco-Shield®	1/50	3500	82	900	10000	5.2"
T4	13	G24q-1	109039	PL13D/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	900	10000	5.2"
T4	13	G24q-1	109122	PL13D/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	900	10000	5.2"
T4	18	G24q-2	109010	PL18D/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	1200	10000	5.8"
T4	18	G24q-2	109012	PL18D/E/35	White EOL Eco-Shield®	1/50	3500	82	1200	10000	5.8"
T4	18	G24q-2	109013	PL18D/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	1200	10000	5.8"
T4	18	G24q-2	109074	PL18D/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	1200	10000	5.8"
T4	26	G24q-3	109090	PL26D/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	1800	10000	6.5"
T4	26	G24q-3	109092	PL26D/E/35	White EOL Eco-Shield®	1/50	3500	82	1800	10000	6.5"
T4	26	G24q-3	109094	PL26D/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	1800	10000	6.5"
T4	26	G24q-3	109096	PL26D/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	1800	10000	6.5"

Bulb Type	Watts	Base	Item #	Product Code	Description	Pkg/ Qty	Color Temp	CRI	Initial Lumens	Avg Rated Life	MOL (Inches)
<b>TRIPLE TUBE 4-PIN ELECTRONIC</b>											
T4	18	GX24q-2	44800	PL18T/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	1200	10000	4.6"
T4	18	GX24q-2	44801	PL18T/E/35	White EOL Eco-Shield®	1/50	3500	82	1200	10000	4.6"
T4	18	GX24q-2	44803	PL18T/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	1200	10000	4.6"
T4	18	GX24q-2	44804	PL18T/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	1200	10000	4.6"
T4	26	GX24q-3	109020	PL26T/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	1800	10000	5.2"
T4	26	GX24q-3	109022	PL26T/E/35	White EOL Eco-Shield®	1/50	3500	82	1800	10000	5.2"
T4	26	GX24q-3	109024	PL26T/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	1800	10000	5.2"
T4	26	GX24q-3	109076	PL26T/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	1800	10000	5.2"
T4	32	GX24q-3	109026	PL32T/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	2400	10000	5.8"
T4	32	GX24q-3	109028	PL32T/E/35	White EOL Eco-Shield®	1/50	3500	82	2400	10000	5.8"
T4	32	GX24q-3	109030	PL32T/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	2400	10000	5.8"
T4	32	GX24q-3	109070	PL32T/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	2400	10000	5.8"
T4	42	GX24q-4	109032	PL42T/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	3200	10000	6.6"
T4	42	GX24q-4	109034	PL42T/E/35	White EOL Eco-Shield®	1/50	3500	82	3200	10000	6.6"
T4	42	GX24q-4	109036	PL42T/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	3200	10000	6.6"
T4	42	GX24q-4	109072	PL42T/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	3200	10000	6.6"
T4	57	GX24q-5	44806	PL57T/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	4200	10000	7.8"
T4	57	GX24q-5	44807	PL57T/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	4200	10000	7.8"
T4	57	GX24q-5	44808	PL57T/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	4200	10000	7.8"
<b>SPIRAL TUBE 4-PIN ELECTRONIC</b>											
T4	13	GX24q-1	109692	PL13SP/E/27	Warm White	1/50	2700	82	900	10000	3.5"
T4	13	GX24q-1	109694	PL13SP/E/41	Cool White	1/50	4100	82	900	10000	3.5"
T3	26	G24q-3	109696	PL26SP/E/27	Warm White	10/50	2700	82	1600	10000	4.1"
T3	26	G24q-3	109698	PL26SP/E/41	Cool White	10/50	4100	82	1600	10000	4.1"
<b>FLAT QUAD 4-PIN</b>											
T4	27	GX10q-4	109238	FML27/NDL	Warm White	1/50	5000	82	1500	10000	5.9"
<b>R40 4-PIN ELECTRONIC</b>											
R40	26	G24q-3	109382	PL26/R40/E/30	Soft White Flood	6/24	3000	82	1450	8000	6.1"
R40	26	G24q-3	109388	PL26/R40/E/50	Natural White Flood	6/24	5000	82	1450	8000	6.1"

 Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.  
 Visit [www.lamprecycle.org](http://www.lamprecycle.org) for disposal information for your state or local government.