

TECHNICAL DATA SHEET

FEATURES

- · Light weight and has a low profile
- Excellent color rendition
- · Light instantly, no flicker
- · Less heat output with a low starting temperature

APPLICATION

Available in a full selection of sizes and designs that allow a convenient fit for nearly every style of fixture. Used for decorative and orientation lighting.

PLC 2 PIN CFL **PLC LAMP**

20234

PRODUCT DETAILS

ELECTRICAL	
Wattage	26W
Voltage	120V
LIGHTING PERFORMANCE	
Mean Lumens	1560
Lumens Per Watt (Lm/W)	60
Color Temperature (CCT)	3000K
Color Rendering (CRI)	80
Dimmable Lighting Control	
LIFESPAN	
Average Life (Hours)	12,000
Warranty (Years)	5
CONSTRUCTION	
Housing	Glass / Plastic
Base / Power Supply	G24D-3
Finish	White
Mercury Content (Hg)	2.2mg

PACKAGING	
Master Carton	200pc / 811768023203
Inner Carton	50pc / 811768023200
Individual Box	811768023206
Country of Origin	China
HS Tariff	8539.31.0050
DIMENSIONS	
Dimensions (Inches)	6.8"(L) x 1.4"(DIA)

ORDERING

ITEM#	DESCRIPTION	CASE
20234	PLC26/30K/G24D-3	50/200

Published lumens on products are approximate and may vary slightly.

This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.