



GE  
Lighting

**97609 - F26DBX/841/ECO**

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse



High Color Rendering  
Energy Savings

Photo  
Not Available




Photo  
Not Available



Photo  
Not Available

**CAUTIONS & WARNINGS**

**Caution**

- Lamp may shatter and cause injury if broken
  - Remove and install by grasping only plastic portion of the lamp.

**NOTES**

- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life

**GENERAL CHARACTERISTICS**

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T4
Base	G24d-3
Equivalent Wattage (NOM)	100.0 W
Rated Life (NOM)	10000.0 h
Starting Temperature (MIN)	-9.0 °C
Cathode Resistance (NOM)	2.7 Ohm
Mercury Content (NOM)	3.0 mg
Picograms of Mercury (NOM)	205.4794 pg
Additional Info	TCLP compliant
Primary Application	Facilities;Retail Display;Hospitality;Office;Restaurant;Warehouse

**PHOTOMETRIC CHARACTERISTICS**

Initial Lumens (NOM)	1710.0
Mean Lumens (NOM)	1460.0
Nominal Initial Lumens per Watt (NOM)	65.76923
Color Temperature (NOM)	4100.0 K
Color Rendering Index (CRI) (NOM)	82.0

**ELECTRICAL CHARACTERISTICS**

Wattage (NOM)	26.0
Voltage (NOM)	105.0
Open Circuit Voltage Across Starter (MIN)	198.0 V
Lamp Current (NOM)	0.325 A
Current Crest Factor (MAX)	1.7
Supply Current Frequency (NOM)	60.0 Hz

**DIMENSIONS**

Maximum Overall Length (MOL) (NOM)	6.670 in(169.4 mm)
Nominal Length (NOM)	6.700 in(170.2 mm)
Base Face to Top of Lamp (NOM)	5.790 in(147.1 mm)

**PRODUCT INFORMATION**

Product Code	97609
Description	F26DBX/841/ECO
ANSI Code	60901-IEC-0526-2
Standard Package	BUNDLE
Standard Package GTIN	
Standard Package Quantity	50
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
UPC	043168976091