# **DesignLights Consortium**





Classification	Premium
Primary Use	Architectural Flood and Spot Luminaires
Reported Input Wattage	35.8 W
Reported Light Output	4585 lm
Reported CCT	3000 K
Reported CRI (Ra)	83
Product ID	S-MJT1S2
DLC Family Code	EMWAOO
Listing Status	Listed
Date Qualified	2022-05-19

# **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting		
Technical Requirements Version	5.1		
Product ID	S-MJT1S2		
Manufacturer	Precision Lighting & Transformer, Inc		
Brand	PLT Solutions		
Model Number	PLTSNH131Y5[1;2;Blank][1;Blank][1;3;2;4]		
Parent	No		
Classification	Premium		
DLC Family Code	EMWAOO		
Input Power Type	AC		

# PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	Low Output	
Primary Use Designation	Architectural Flood and Spot Luminaires	

#### **PRODUCT CAPABILITIES VIEW DETAILS**

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Exterior Photocell
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

# REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

4595 lm
4585 lm
128.01 lm/W
3000 K
83
9
85
97
-11
4480 lm
4585 lm
3000 K
5000 K
4585 lm

# REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	35.8 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Maximum Input Wattage	35.8
Reported Default Input Wattage	35
Voltage Range	120-277 V

# **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Field Adjustable Light Distribution Setting	No restriction

### VERSION HISTORY VIEW DETAILS

2022-05-19	Listed	5.1	Premium
------------	--------	-----	---------