



ProLume.
◀ Plug-Ins

COMPACTS

ProLume® Plug-Ins



Energy Efficient

- Save up to 80% in energy costs compared to standard incandescent lamps
- Tri-phosphor coating enhances lumen efficacy and color rendering, 82 CRI

Technical Data

- Operating temperature 0 - 140°F
- Lead-free glass
- End-of-Life protection

Broad Assortment

- Single and Double Tube 2-Pin
- Single, Double, Triple and Spiral Tube 4-Pin
- Flat Quad 4-Pin
- 2700, 3500, 4100 and 5000K

Long Life


- 10,000 Hours Average Rated Life
- 1-Year Guarantee

Benefits

- Saves energy
- Low maintenance
- Excellent color rendering
- TCLP compliant

Applications

- Wall sconces
- Down lighting
- Task lighting
- Security

The **Eco-Shield®**  mark indicates this product is TCLP compliant.

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at halcolighting.com.

Your account representative is your single source for pricing, orders, and technical support.

Shipping from Atlanta, Cleveland, Houston, and Phoenix.

ISO 9001 Certified




**where there's light,
there's halco®**

(800) 677-3334

halcolighting.com

Bulb Type	Watts	Base	Item #	Product Code	Description	Pkg/Qty	Color Temp	CRI	Initial Lumens	Avg Rated Life	MOL (Inches)
SINGLE TUBE 2-PIN											
T4	5	G-23	109100	PL5S/27	Warm White EOL	1/50	2700	82	250	10000	4.3"
T4	5	G-23	109102	PL5S/41	Cool White EOL	1/50	4100	82	250	10000	4.3"
T4	7	G-23	109106	PL7S/27	Warm White EOL	1/50	2700	82	400	10000	5.4"
T4	7	G-23	109107	PL7S/35	White EOL	1/50	3500	82	400	10000	5.4"
T4	7	G-23	109108	PL7S/41	Cool White EOL	1/50	4100	82	400	10000	5.4"
T4	9	G-23	109112	PL9S/27	Warm White EOL	1/50	2700	82	600	10000	6.6"
T4	9	G-23	109144	PL9S/35	White EOL	1/50	3500	82	600	10000	6.6"
T4	9	G-23	109116	PL9S/41	Cool White EOL	1/50	4100	82	600	10000	6.6"
T4	9	G-23	109118	PL9S/50	Natural White EOL	1/50	5000	82	600	10000	6.6"
T4	13	GX23	109126	PL13S/27	Warm White EOL Eco-Shield®	1/50	2700	82	825	10000	7.2"
T4	13	GX23	109128	PL13S/35	White EOL Eco-Shield®	1/50	3500	82	825	10000	7.2"
T4	13	GX23	109130	PL13S/41	Cool White EOL Eco-Shield®	1/50	4100	82	825	10000	7.2"
T4	13	GX23	109132	PL13S/50	Natural White EOL Eco-Shield®	1/50	5000	82	825	10000	7.2"
DOUBLE TUBE 2-PIN											
T4	9	G23-2	109110	PL9D/27	Warm White EOL	1/50	2700	82	525	10000	4.3"
T4	9	G23-2	109120	PL9D/41	Cool White EOL	1/50	4100	82	525	10000	4.3"
T4	13	GX23-2	109146	PL13D/27	Warm White EOL Eco-Shield®	1/50	2700	82	900	10000	4.7"
T4	13	GX23-2	109148	PL13D/35	White EOL Eco-Shield®	1/50	3500	82	900	10000	4.7"
T4	13	GX23-2	109150	PL13D/41	Cool White EOL Eco-Shield®	1/50	4100	82	900	10000	4.7"
T4	13	GX23-2	109149	PL13D/50	Natural White EOL Eco-Shield®	1/50	5000	82	900	10000	4.7"
T4	18	G24d-2	109152	PL18D/27	Warm White EOL	1/50	2700	82	1200	10000	6.0"
T4	18	G24d-2	109154	PL18D/35	White EOL	1/50	3500	82	1200	10000	6.0"
T4	18	G24d-2	109156	PL18D/41	Cool White EOL	1/50	4100	82	1200	10000	6.0"
T4	18	G24d-2	109159	PL18D/50	Natural White EOL	1/50	5000	82	1200	10000	6.0"
T5	22	GX32d-2	109862	PL22D/27	Warm White	1/50	2700	82	1200	10000	6.1"
T5	22	GX32d-2	109864	PL22D/50	Natural White	1/50	5000	82	1200	10000	6.1"
T4	26	G24d-3	109158	PL26D/27	Warm White EOL Eco-Shield®	1/50	2700	82	1800	10000	6.8"
T4	26	G24d-3	109160	PL26D/35	White EOL Eco-Shield®	1/50	3500	82	1800	10000	6.8"
T4	26	G24d-3	109162	PL26D/41	Cool White EOL Eco-Shield®	1/50	4100	82	1800	10000	6.8"
T4	26	G24d-3	109163	PL26D/50	Natural White EOL Eco-Shield®	1/50	5000	82	1800	10000	6.8"
T5	28	GX32d-3	109870	PL28D/28	Warm White	10/50	2800	82	1600	10000	6.7"
T5	28	GX32d-3	109868	PL28D/50	Natural White	10/50	5000	82	1600	10000	6.7"
SINGLE TUBE 4-PIN ELECTRONIC											
T4	13	2GX7	109134	PL13S/E/27	Warm White EOL	1/50	2700	82	825	10000	6.7"
T4	13	2GX7	109136	PL13S/E/35	White EOL	1/50	3500	82	825	10000	6.7"
T4	13	2GX7	109138	PL13S/E/41	Cool White EOL	1/50	4100	82	825	10000	6.7"
T4	13	2GX7	109140	PL13S/E/50	Natural White EOL	1/50	5000	82	825	10000	6.7"
DOUBLE TUBE 4-PIN ELECTRONIC											
T4	13	G24q-1	109037	PL13D/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	900	10000	5.2"
T4	13	G24q-1	109035	PL13D/E/30	Soft White EOL Eco-Shield®	1/50	3000	83	900	10000	5.2"
T4	13	G24q-1	109038	PL13D/E/35	White EOL Eco-Shield®	1/50	3500	82	900	10000	5.2"
T4	13	G24q-1	109039	PL13D/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	900	10000	5.2"
T4	13	G24q-1	109122	PL13D/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	900	10000	5.2"
T4	18	G24q-2	109010	PL18D/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	1200	10000	5.8"
T4	18	G24q-2	109012	PL18D/E/35	White EOL Eco-Shield®	1/50	3500	82	1200	10000	5.8"
T4	18	G24q-2	109013	PL18D/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	1200	10000	5.8"
T4	18	G24q-2	109074	PL18D/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	1200	10000	5.8"
T4	26	G24q-3	109090	PL26D/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	1800	10000	6.5"
T4	26	G24q-3	109092	PL26D/E/35	White EOL Eco-Shield®	1/50	3500	82	1800	10000	6.5"
T4	26	G24q-3	109094	PL26D/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	1800	10000	6.5"
T4	26	G24q-3	109096	PL26D/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	1800	10000	6.5"

Bulb Type	Watts	Base	Item #	Product Code	Description	Pkg/ Qty	Color Temp	CRI	Initial Lumens	Avg Rated Life	MOL (Inches)
TRIPLE TUBE 4-PIN ELECTRONIC											
T4	18	GX24q-2	44800	PL18T/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	1200	10000	4.6"
T4	18	GX24q-2	44801	PL18T/E/35	White EOL Eco-Shield®	1/50	3500	82	1200	10000	4.6"
T4	18	GX24q-2	44803	PL18T/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	1200	10000	4.6"
T4	18	GX24q-2	44804	PL18T/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	1200	10000	4.6"
T4	26	GX24q-3	109020	PL26T/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	1800	10000	5.2"
T4	26	GX24q-3	109022	PL26T/E/35	White EOL Eco-Shield®	1/50	3500	82	1800	10000	5.2"
T4	26	GX24q-3	109024	PL26T/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	1800	10000	5.2"
T4	26	GX24q-3	109076	PL26T/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	1800	10000	5.2"
T4	32	GX24q-3	109026	PL32T/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	2400	10000	5.8"
T4	32	GX24q-3	109028	PL32T/E/35	White EOL Eco-Shield®	1/50	3500	82	2400	10000	5.8"
T4	32	GX24q-3	109030	PL32T/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	2400	10000	5.8"
T4	32	GX24q-3	109070	PL32T/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	2400	10000	5.8"
T4	42	GX24q-4	109032	PL42T/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	3200	10000	6.6"
T4	42	GX24q-4	109034	PL42T/E/35	White EOL Eco-Shield®	1/50	3500	82	3200	10000	6.6"
T4	42	GX24q-4	109036	PL42T/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	3200	10000	6.6"
T4	42	GX24q-4	109072	PL42T/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	3200	10000	6.6"
T4	57	GX24q-5	44806	PL57T/E/27	Warm White EOL Eco-Shield®	1/50	2700	82	4200	10000	7.8"
T4	57	GX24q-5	44807	PL57T/E/41	Cool White EOL Eco-Shield®	1/50	4100	82	4200	10000	7.8"
T4	57	GX24q-5	44808	PL57T/E/50	Natural White EOL Eco-Shield®	1/50	5000	82	4200	10000	7.8"
SPIRAL TUBE 4-PIN ELECTRONIC											
T4	13	GX24q-1	109692	PL13SP/E/27	Warm White	1/50	2700	82	900	10000	3.5"
T4	13	GX24q-1	109694	PL13SP/E/41	Cool White	1/50	4100	82	900	10000	3.5"
T3	26	G24q-3	109696	PL26SP/E/27	Warm White	10/50	2700	82	1600	10000	4.1"
T3	26	G24q-3	109698	PL26SP/E/41	Cool White	10/50	4100	82	1600	10000	4.1"
FLAT QUAD 4-PIN											
T4	27	GX10q-4	109238	FML27/NDL	Warm White	1/50	5000	82	1500	10000	5.9"
R40 4-PIN ELECTRONIC											
R40	26	G24q-3	109382	PL26/R40/E/30	Soft White Flood	6/24	3000	82	1450	8000	6.1"
R40	26	G24q-3	109388	PL26/R40/E/50	Natural White Flood	6/24	5000	82	1450	8000	6.1"

 Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.
Visit www.lamprecycle.org for disposal information for your state or local government.