

97616 - F26TBX/835/A/ECO

GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse










CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Remove and install by grasping only plastic portion of the lamp.

GRAPHS & CHARTS

Graphs_Spectral Power Distribution



GENERAL CHARACTERISTICS

Lamp Type Compact Fluorescent - Plug-In

 $\begin{array}{ccc} \text{Bulb} & \text{T4} \\ \text{Base} & \text{GX24q-3} \\ \text{Rated Life} & 17000.0 \text{ hrs} \\ \text{Starting Temperature (MIN)} & 0.0 \text{ K} \\ \text{Cathode Resistance} & 2.7 \text{ Ohm} \end{array}$

LEED-EB MR Credit 115 picograms Hg per mean

lumen hour

Rated Life (rapid start) @ Time 17000.0 @ 3.0/20000.0 @

12.0 h

Additional Info

Dimmable with appropriate dimming ballast./End of

Life Protection (EOL)/TCLP

compliant

Primary Application Facilities; Retail; Display; Hospitality; Office;

Restaurant; Warehouse

PHOTOMETRIC CHARACTERISTICS

Initial Lumens 1800.0
Mean Lumens 1530.0
Nominal Initial Lumens per Watt 69
Color Temperature 3500.0 K
Color Rendering Index (CRI) 82.0

ELECTRICAL CHARACTERISTICS

 Wattage
 26.0

 Voltage
 120.0

 Current (max)
 5.25 A

 Open Circuit Voltage (after
 265.0 V

preheating) (MAX)

Open Circuit Voltage Across 198.0 V

Starter (MIN)

Lamp Current 0.325 A
Preheat Voltage (MIN) 4.25 V
Current Crest Factor (MAX) 1.7

Supply Current Frequency 20000.0 Hz

DIMENSIONS

Maximum Overall Length 5.2000 in(132.1 mm)

(MOL)

Nominal Length 5.200 in(132.1 mm)

Base Face to Top of Lamp 4.6 cm

PRODUCT INFORMATION

Product Code 97616

Description F26TBX/835/A/ECO ANSI Code 60901-IEC-3426-1

Standard Package Case

Standard Package GTIN 10043168976166

Standard Package Quantity
Sales Unit
No Of Items Per Sales Unit
No Of Items Per Standard

10

Package

UPC 043168976169

NOTES

- 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).
- Amalgam product experience stable brightness over a wider temperature range and in various operating positions.
- Based on 60Hz reference circuit.
- Fluorescent lamp lumens decline during life