



DESCRIPTION

Greatly reduce energy and maintenance costs by replacing existing fluorescent strip fixtures with these more efficient wattage and color selectable LED strip light fixtures.

FEATURES

- Efficiently replaces a 3 lamp fluorescent fixture
- Delivers up to 130 LPW; output will vary depending on the wattage selected
- 0-10V dimming
- Wattage and color temperature are adjusted via dip switches on the driver; see installation instructions for more details

LISTINGS

- UL rated for damp locations
- DesignLights Consortium® 5.1 Standard meets the requirements for the highest DLC qualification for efficacy and lumen maintenance; DLC PN - PLTM349142

PERFORMANCE

• CRI: >80

CCT: 3500K, 4000K, and 5000KRated Lifetime L70: 50,000 hours

THERMAL

-4°F to 122°F (-20°C to 50°C) operating temperature

ELECTRICAL

• THD: < 20%

Power Factor: 0.9

Input Voltage: 120-277V

Dimmable power supply (0-10V)

INSTALLATION

 Designed for surface mounting (mounting hardware included) or suspension (v-hooks and chain sold separately); see installation instructions for more details

CONSTRUCTION

- Steel plate housing with white finish
- PMMA lens protects LEDs while evenly distributing light

WARRANTY

 5 year limited warranty; see pltsolutions.com for warranty details

| project name | type | | |
|----------------|---------|--|--|
| catalog number | | | |
| comments | voltage | | |
| approved by | date | | |








APPLICATIONS

- Storage Areas
- Utility Areas
- Garages
- Workshops
- Hallways

PERFORMANCE SUMMARY

| Item# | Watts | Lumens | LPW | ССТ | CRI | Dimming | Voltage | Replaces | DLC Rating | DLC # |
|------------|----------|----------------|-------------|-------------------|-----|---------|----------|--------------------|---------------|------------|
| PLTS-40050 | 34/38/45 | 4760/5206/5895 | 131/137/140 | 3500K/4000K/5000K | >80 | 0-10V | 120-277V | 3 Lamp Fluorescent | 5.1 Standard | PLTM349142 |

DIMENSIONS



DIMENSIONS

Length: 47.3" Height: 2.8" Width: 2.4"

Weight: 3.7 lbs.

PHOTOMETRICS

