

# 97631 - GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse F32TBX/835/A/ECO

# **Product Photo**



# **CAUTIONS & WARNINGS**

#### Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

Oct 19, 2015 6:07:28 PM For additional information, visit www.gelighting.com

## **GENERAL CHARACTERISTICS**

Base Type Mercury Content Rated Life Hours-nominal Starting Temp (MIN) C-degrees Mercury-Picogrm per mean Im hr Primary Application

Product Technology Base **Bulb Shape** 

### PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal Nominal Initial Lumen per Watt Initial Lumens-nominal Color Rendering Index-CRI Color Temperature

#### **PRODUCT INFORMATION**

Product Code	976
Description	F32
Alternative Unit Of Measure	Cas
Standard Package Quantity	10
Ean UPC	043
Standard Package GTIN	100
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	10
Sales Unit	Un
UCC	043

# DIMENSIONS

Base Face to Top of Lamp 4.9 in Nominal Length Bulb Max Overall Length-MOL

### **ELECTRICAL CHARACTERISTICS**

Equivalent Incandescent Watts	150 W
Current Crest Factor (MAX)	5.25
Supply Current Freq nominal Hz	20 Hz
Rated power (Watts)	32 W

Pin/Plug-In 3 mg 17000 h 0°C 86.5 Facilities Retail Display Hospitality Office Restaurant Warehouse **Compact Fluorescent** GX24q-3 Τ3

631 2TBX/835/A/ECO ase 3168976312 043168976319 nit 3168976312

5.5 in 5.5 in