

Features/Benefits

- High lumen Output in a slim, compact size.
- Broad range of available wattages: 18, 24, 36, 40, 50, 55, and 80W.
- Excellent Color Rendering 82 Color Rendering Index (CRI); 55W available with 91 CRI.
- Available in 3000, 3500 and 4100K; 55W available as 5000K only.
- Dimmable PL-L 4-pin lamps may be used with electronic dimming ballasts.
- Long life: 15,000 to 20,000 hours average life depending on wattage.

Applications

• Ideal for commercial interior lighting applications in 2'x2' fixtures, 1'x2' fixtures, and indirect lighting.


Notes


- Rated average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Lamp life is appreciably longer if lamps are started less frequently. (202)
- Approximate Initial Lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life, when the output is measured during operation on a reference ballast under standard laboratory conditions. (203)
- Design Lumens are the approximate lamp lumen output at 40% of the lamp's Rated Average Life. This output is based upon measurements obtained during lamp operation on a reference ballast under standard laboratory conditions. (208)

Product data		
ProNumUS	300434	
Full product name	PL-L 40W/835/4P 1CT	
OrdCodUS	300434	
Pack type	1 Lamp in a Folding Carton	
Pieces per Sku	1	
Skus/Case	25	
EAN1US		
EAN2US		
EAN3US		
Successor Product number		



Product data		
System Description	Rapid Start	
Base	2G11	
Base Information	4P	
Execution	/4P [4 Pins]	
Packing Type	1CT [1 Lamp in a Folding Carton]	
Packing Configuration	25	
Avg. Life	10000 hr	
Avg. Hrs. Life	- hr	
Ordering Code	PL-L 40W/835/4P RS/IS	
Pack UPC	046677111793	
Case Bar Code	50046677111798	
Watts	40W	
Lamp Voltage	126 V	
Dimmable	Yes	
Color Code	835 [CCT of 3500K]	
Color Rendering Index	82 Ra8	
Color Designation	White	
Color Description	35 White	
Color Temperature	3500 K	
Initial Lumens	3500 Lm	
Overall Length C	571.6 mm	
Diameter D	39 mm	
Diameter D1	18 mm	
Product Number	300434	







Base 2G11




PL-L





PL-L/835

PL-L



PL-L/835

