

DesignLights Consortium



Classification	Standard
Primary Use	Direct Linear Ambient Luminaires
Reported Input Wattage	45 W
Reported Light Output	5850 lm
Reported CCT	4000 K
Reported CRI (Ra)	82
Product ID	PLMG1HTTS3T3
DLC Family Code	DDDKUH
Listing Status	Listed
Date Qualified	2019-01-03

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLMG1HTTS3T3
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM242122
Parent	No
Classification	Standard
DLC Family Code	DDDKUH
Length	4.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Linear Ambient
Primary Use Designation	Direct Linear Ambient Luminaires

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5850 lm
Reported Efficacy (AC)	130 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	82
Reported R9	12
Reported IES Rf	80
Reported IES Rg	90
Reported IES Rcs,h1	-12
Reported Default Light Output	5850 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	45 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.9
Reported Default Input Wattage	45
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2022-08-16	Listed	5.1	Standard
2022-06-30	Delisted	5	Premium
2020-03-30	Listed	5	Premium

2020-01-03	Listed	4.4	Premium
------------	--------	-----	---------