

Project Name:	Type:
Part Number:	Date:



GREENCREATIVE

COMPACT HID REPLACEMENT BULB

FEATURES

- Integral driver suitable for 120-277V
- Integral thermal sensor reduces power to the lamp in the event ambient temperature exceeds specified limitations
- E26 versions are smooth dimming with existing installations*
- EX39 versions are step-dimming using SelectDrive technology
- A21 replaces up to 125W Inc.
- A23 replaces up to 200W Inc.
- PS30 replaces up to 100-175W HID, E26 version replaces up to 300W Inc.
- Suitable for damp locations and totally enclosed fixtures**
- Lamp ambient temperature: -4°F to 140°F (-20°C to 60°C)
- Fixture operating temperature: -4°F to 113°F (-20°C to 45°C)
- Rated lifetime (L70): 50,000hrs
- 5 year limited warranty***
- Supplied with safety cable to provide secondary support for A23 and PS30
- 4kV integral surge protector
- For installation in Post Top, Area light, or other fixtures exposed to high surge conditions, the use of our 10KV surge protector 97718-10SURGE/277V is recommended.



060523

ETL CLASSIFIED



FOCUS FEATURE

EX39 version has integrated side switch for step-dimming



H
M
L

3 Level power output

Power select switch allows power to be tailored to application requirements and can be adjusted from high to low.



	CCT	Wattage	Lumen	LPW
34HID/8xx/277V/EX39/SD	3000K	40%-13.6W	1,800	132
		60%-20.4W	2,700	132
		100%-34W	4,500	132
	4000K	40%-13.6W	2,000	147
		60%-20.4W	3,000	147
		100%-34W	5,000	147
	5000K	40%-13.6W	2,000	147
		60%-20.4W	3,000	147
		100%-34W	5,000	147

	CCT	Wattage	Lumen	LPW
24HID/8xx/277V/EX39/SD	3000K	40%-9W	1,250	139
		60%-14W	1,850	132
		100%-24W	3,100	129
	3500K	40%-9W	1,250	139
		60%-14W	1,850	132
		100%-24W	3,100	129
	4000K	40%-9W	1,300	144
		60%-14W	1,900	136
		100%-24W	3,200	133
5000K	40%-9W	1,300	144	
	60%-14W	1,900	136	
	100%-24W	3,200	133	

Where xxx means 824-965 which indicates CRI and color temperature



COMPACT HID REPLACEMENT BULB


SPECIFICATIONS

Product	Model	Equiv.	Input Voltage	Wattage	Lumens	CCT	CRI	Efficacy (LPW)	Beam Angle	Dim.*	Power Factor	THD	Fixture Rating	DLC / ES
36165	17A21/830/277V/DIM	125W Inc.	120-277V	17	2,000	3000K	82	118	230°	Yes	0.9	<20%	Enclosed	N.A. / √
36166	17A21/835/277V/DIM	125W Inc.	120-277V	17	2,000	3500K	82	118	230°	Yes	0.9	<20%	Enclosed	N.A. / √
36167	17A21/840/277V/DIM	125W Inc.	120-277V	17	2,100	4000K	82	124	230°	Yes	0.9	<20%	Enclosed	N.A. / √
36168	17A21/850/277V/DIM	125W Inc.	120-277V	17	2,100	5000K	82	124	230°	Yes	0.9	<20%	Enclosed	N.A. / √
36169	24HID/830/277V/E26/DIM	200W Inc.	120-277V	24	3,100	3000K	82	129	230°	Yes	0.9	<20%	Enclosed	N.A. / √
36214	24HID/835/277V/E26/DIM	200W Inc.	120-277V	24	3,100	3500K	82	129	230°	Yes	0.9	<20%	Enclosed	N.A. / √
36170	24HID/840/277V/E26/DIM	200W Inc.	120-277V	24	3,200	4000K	82	133	230°	Yes	0.9	<20%	Enclosed	N.A. / √
36171	24HID/850/277V/E26/DIM	200W Inc.	120-277V	24	3,200	5000K	82	133	230°	Yes	0.9	<20%	Enclosed	N.A. / √
36158	24HID/830/277V/EX39/SD	70-100W HID	120-277V	24	3,100	3000K	82	139	230°	No	0.9	<20%	Enclosed	√ / N.A.
36159	24HID/835/277V/EX39/SD	70-100W HID	120-277V	24	3,100	3500K	82	139	230°	No	0.9	<20%	Enclosed	√ / N.A.
36160	24HID/840/277V/EX39/SD	70-100W HID	120-277V	24	3,200	4000K	82	144	230°	No	0.9	<20%	Enclosed	√ / N.A.
36161	24HID/850/277V/EX39/SD	70-100W HID	120-277V	24	3,200	5000K	82	144	230°	No	0.9	<20%	Enclosed	√ / N.A.
36173	34HID/840/277V/E26/DIM	300W Inc.	120-277V	34	5,000	4000K	82	147	230°	Yes	0.9	<20%	Enclosed	N.A. / √
36174	34HID/850/277V/E26/DIM	300W Inc.	120-277V	34	5,000	5000K	82	147	230°	Yes	0.9	<20%	Enclosed	N.A. / √
36163	34HID/840/277V/EX39/SD	100-175W HID	120-277V	34	5,000	4000K	82	147	230°	No	0.9	<20%	Enclosed	√ / N.A.
36164	34HID/850/277V/EX39/SD	100-175W HID	120-277V	34	5,000	5000K	82	147	230°	No	0.9	<20%	Enclosed	√ / N.A.



*This lamp is available for dimming with 120V line voltage only and might not be compatible with all dimmers. Please visit www.greencreative.com for compatibility information.

***Please visit www.greencreative.com for Limited Warranty terms.



DIMENSION & WEIGHT



Model	Base	Mol.	Dia.	Weight
17A21/xxx/277V/DIM	E26	5-1/4"	2-5/8"	2-5/8"



Model	Base	Mol.	Dia.	Weight
24HID/xxx/277V/E26/DIM	E26	6-5/8"	3-5/16"	0.82 lb
24HID/xxx/277V/EX39/SD	EX39	6-11/16"	3-5/16"	0.87 lb



Model	Base	Mol.	Dia.	Weight
34HID/xxx/277V/E26/DIM	E26	8-1/8"	3-3/4"	1.42 lb
34HID/xxx/277V/EX39/SD	EX39	8-1/8"	3-3/4"	1.49 lb

Where xxx means 824-965 which indicates CRI and color temperature




COMPACT HID REPLACEMENT BULB


ORDERING INFORMATION



Model Number	Master Carton			Shipping Carton		
	Case Qty	Case Dimensions (LxWxH)	Case Weight	Case Qty	Case Dimensions (LxWxH)	Case Weight
17A21/xxx/277V/DIM	6PCS	8-15/16"x 6-1/4" x 6-1/2"	3.5 lb	24PCS	12-7/8" x 9-5/16" x 13-3/4"	15 lb
24HID/xxx/277V/E26/DIM	6PCS	11-1/4" x 7-9/16" x 7-13/16"	6.4 lb	24PCS	15-1/2" x 11-9/16" x 8-7/16"	13.4 lb
24HID/xxx/277V/EX39/SD	6PCS	11-1/8" x 7-1/2" x 7-7/8"	7.5lb	24PCS	15-1/2" x 11-3/4" x 8-7/16"	15.2lb
34HID/xxx/277V/E26/DIM	N.A.	N.A.	N.A.	12PCS	16-9/16" x 12-3/8" x 9-9/16"	21.2 lb
34HID/xxx/277V/EX39/SD	N.A.	N.A.	N.A.	12PCS	16-9/16" x 12-3/8" x 9-9/16"	22.1 lb

Where xxx means 824-965 which indicates CRI and color temperature

**MINIMUM COMPARTMENT DIMENSIONS (FOR ENCLOSED FIXTURES)


Low bay installation 	Model Number		24HID/xxx/277V/EX39/SD	34HID/xxx/277V/EX39/SD	
	Lamp Compartment Dimensions	Diameter	Height	6"	8"
			Height	8-1/2"	11"
Maximum Lamps in Luminaire			1	1	

Post top installation 	Model Number		24HID/xxx/277V/EX39/SD	34HID/xxx/277V/EX39/SD	
	Lamp Compartment Dimensions	Diameter	Height	3-9/16"	8"
			Height	7-7/8"	11"
Maximum Lamps in Luminaire			1	1	







		Model Number	17A21/xxx/277V/DIM	24HID/xxx/277V/E26/DIM	34HID/xxx/277V/E26/DIM
Low bay installation 	Lamp Compartment Dimensions	Diameter	6"	6"	8"
		Height	8-1/2"	8-1/2"	11"
Post top installation 	Lamp Compartment Dimensions	Diameter	3-9/16"	3-9/16"	8"
		Height	7-7/8"	7-7/8"	11"
Maximum Lamps in Luminaire			1	1	1

**Installing lamp in a fixture that does not have the minimum compartment dimensions will void the warranty and could cause product failures.

SUPPLIED ACCESSORY

Description	Picture	Dimensions
Safety Cable		22-13/16"

COMPACT HID REPLACEMENT BULB

OPTIONAL ACCESSORY ORDERING INFORMATION				
Product	Model	Description	Picture	Dimensions
97718	10SURGE/277V	10 kV Surge Protector (For use in outdoor and other applications subject to high surge conditions)		
16325	E26 EXTENDER	E26 Lamp Extender Adds 1-5/16" to Lamp Height		
35050	E39 EXTENDER	EX39 Lamp Extender Adds 1-11/16" to Lamp Height		

CERTIFICATION INFORMATION				
Product	Model	DLC ID#	ES ID#	
36158	24HID/830/277V/EX39/SD	PLEQ5F7K	N.A.	
36159	24HID/835/277V/EX39/SD	PW8V6BP	N.A.	
36160	24HID/840/277V/EX39/SD	PRDUFT1V	N.A.	
36161	24HID/850/277V/EX39/SD	PLEQ5F7K	N.A.	
36162	34HID/830/277V/EX39/SD	PSE1QG12	N.A.	
36163	34HID/840/277V/EX39/SD	P7TYZ0PO	N.A.	
36164	34HID/850/277V/EX39/SD	PYW8K0EW	N.A.	
36165	17A21/830/277V/DIM	N.A.	2390212	
36166	17A21/835/277V/DIM	N.A.	2390213	
36167	17A21/840/277V/DIM	N.A.	2390214	
36168	17A21/850/277V/DIM	N.A.	2390215	
36169	24HID/830/277V/E26/DIM	N.A.	2390216	
36214	24HID/835/277V/E26/DIM	N.A.	2390217	
36170	24HID/840/277V/E26/DIM	N.A.	2390218	
36171	24HID/850/277V/E26/DIM	N.A.	2390219	
36173	34HID/840/277V/E26/DIM	N.A.	2390221	
36174	34HID/850/277V/E26/DIM	N.A.	2390222	

Note: All rights reserved. All sizes and specifications are subject to change at any time without notice.