

Reduce your energy costs by replacing existing G9 looped base halogen bulbs with these more efficient LED G9 looped base bulbs.

FEATURES

- Replaces a 50W halogen bulb
- Can be safely handled with bare hands
- Ceramic housing is resistant to corrosion
- Dimmable; see dimmer compatibility sheet for a full list of dimmers

LISTINGS

- ETL Listed for indoor, dry locations
- CE
- FCC
- RoHS

PERFORMANCE

- CRI: 80
- CCT: 2700K
- LED L70 Life Hours: ≥100,000 hours

WARRANTY

- 1 year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Under-cabinet Lights
- Sconce and Pendant Fixtures
- Decorative Chandeliers

project name	type
catalog number	
comments	voltage
approved by	date



PERFORMANCE	Power Consumption	4 Watt
	Lumens	470
	Efficacy (LPW)	118
	CRI	80
	Beam Angle	300°
	CCT	2700K
	LED L70 Life Hours	≥100,000
ELECTRICAL	Input Voltage	120V
	Shape	T7
CONSTRUCTION	Base	G9 Looped
	Housing	Ceramic
	Finish	Clear
	Certifications	ETL Listed; CE; FCC
LISTINGS	Material Usage	RoHS – No mercury or lead
	Environment	Indoor/Dry Locations

PERFORMANCE SUMMARY

Item #	Shape	Lumens	Wattage	LPW	Voltage	Replaces	CCT	CRI	Finish	LED L70 Life Hours	Dimmable
PLT-11700-B	T7	470	4W	118	120V	50W Halogen	2700K	80	Clear	≥100,000	Yes

DIMENSIONS



DIMENSIONS

Height: 2.25"

Width: 0.87"

WARNINGS

- Only use this LED G9 bulb with the dimmers listed in the compatibility list. Using this bulb with incompatible dimmers may cause performance issues including humming, buzzing, flickering, and poor dimming performance.
- Not for use in enclosed fixtures.