

LED G9 LOOPED BASE


PLT-11279-8

Reduce your energy costs by replacing existing G9 looped base halogen bulbs with these more efficient LED G9 looped base bulbs.

project name	type
catalog number	
comments	voltage
approved by	date



RoHSZ FC (



FEATURES

- Replaces a 40W halogen bulb
- Can be safely handled with bare hands
- Ceramic housing is resistant to corrosion
- Dimmable; see dimmer compatibility sheet for a full list of dimmers

LISTINGS

- ETL Listed for indoor, dry locations
- CE
- FCC
- RoHS

PERFORMANCE

- CRI: 80
- CCT: 3000K
- LED L70 Life Hours: ≥100,000 hours

WARRANTY

• 1 year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Under-cabinet Lights
- Sconce and Pendant Fixtures
- Decorative Chandeliers

PERFORMANCE	Power Consumption	3.5 Watt			
	Lumens	410			
	Efficacy (LPW)	117			
	CRI	80			
	Beam Angle	300°			
	сст	3000K			
	LED L70 Life Hours	≥100,000			
ELECTRICAL	Input Voltage	120V			
	Shape	T5.5			
CONSTRUCTION	Base	G9 Looped			
CONSTRUCTION	Housing	Ceramic			
	Finish	Clear			
	Certifications	ETL Listed; CE; FCC			
LISTINGS	Material Usage	RoHS – No mercury or lead			
	Environment	Indoor/Dry Locations			

PERFORMANCE SUMMARY

Item #	Shape	Lumens	Wattage	LPW	Voltage	Replaces	ССТ	CRI	Finish	LED L70 Life Hours	Dimmable
PLT-11279-B	T5.5	410	3.5W	117	120V	40W Halogen	3000K	80	Clear	≥100,000	Yes

DIMENSIONS



2.25"

DIMENSIONS

Height: 2.25" Width: 0.71"

WARNINGS

- Only use this LED G9 bulb with the dimmers listed in the compatibility list. Using this bulb with incompatible dimmers may cause performance issues including humming, buzzing, flickering, and poor dimming performance.
- Not for use in enclosed fixtures.