



DESCRIPTION

Replace existing fluorescent wraparound fixtures with these LED wraparound fixtures to reduce maintenance and energy costs.

FEATURES

- Efficiently replaces a 4 lamp fluorescent fixture
- Delivers an impressive 130 LPW
- 0-10V dimming

LISTINGS

- UL rated for damp locations
- RoHS

PERFORMANCE

- CRI: 80+
- CCT: 4000K and 5000K
- LED L70 Life Hours: 100,000

THERMAL

- -4°F to 113°F (-20°C to 45°C) operating temperature

ELECTRICAL

- THD: <20%
- Power Factor: >0.9
- Input Voltage: 120-277V
- Dimmable power supply (0-10V)

INSTALLATION

- Designed for surface or suspension mounting (hardware not included); see installation instructions for more details

CONSTRUCTION

- Steel housing with white finish
- PMMA lens protects LEDs while evenly distributing light

WARRANTY

- 5-year limited warranty; see pltsolutions.com for warranty details

project name	type
catalog number	
comments	voltage
approved by	date




APPLICATIONS

- Stairways
- Bathrooms
- Utility and Storage Areas
- Hallways
- Offices

PERFORMANCE SUMMARY

Item #	Watts	Lumens	LPW	CCT	CRI	Dimming	Voltage	Replaces
PLT-90181	64W	8320	130	4000K	80+	Yes	120-277V	4 Lamp Fluorescent
PLT-90182	64W	8320	130	5000K	80+	Yes	120-277V	4 Lamp Fluorescent

DIMENSIONS



DIMENSIONS

Length: 47.7"

Height: 2.8"

Width: 7.1"

Weight: 7.93 lbs