# **DesignLights Consortium**





Classification	Standard
Primary Use	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	40 W
Reported Light Output	4720 lm
Reported CCT	5000 K
Reported CRI (Ra)	82
Product ID	S-71DI5B
DLC Family Code	OOOBFH
Listing Status	Listed
Date Qualified	2022-10-17

#### **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-71DI5B
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM53455
Parent	Yes
Classification	Standard
DLC Family Code	OOOBFH
Input Power Type	AC

# PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	Troffer	
Primary Use Designation	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces	

#### PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below

https://qpl.designlights.org/solid-state-lighting?search=PLTM52354&dlc\_session\_id=e164942bf6d0d21744a1&dlc\_last\_company\_id=9409

10/19/22, 10:06 AM

DLC Qualified Product List - Solid State Lighting

	5 5
Integral Control Capability	No Control Capability
Sensor Type	Multifunction Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

# **REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Reported Light Output	4720 lm
Reported Efficacy (AC)	118 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	82
Reported R9	11
Reported IES Rf	82
Reported IES Rg	97
Reported IES Rcs,h1	-12
Reported Default Light Output	4720 lm

# **REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS**

Reported Input Wattage	40 W
Reported Total Harmonic Distortion	11.2 %
Reported Power Factor	0.955
Reported Default Input Wattage	40
Voltage Range	120-277 V

#### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Tested Light Output	4822 lm
Tested Efficacy (AC)	126.32 lm/W
Tested CCT	4929 K
Tested CRI (Ra)	82
Tested R9	10
Tested IES Rf	82
Tested IES Rg	97
Tested IES Rcs,h1	-12 %
Tested Duv	-0.00056

#### **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

Tested Voltage	120
Tested Input Wattage	38.2 W
Tested Total Harmonic Distortion	11.5 %
Tested Power Factor	0.955

#### **VERSION HISTORY VIEW DETAILS**

2022-10-17	Listed	5.1	Standard
------------	--------	-----	----------