

## DESCRIPTION

Featuring a low-profile design, this 150W UFO LED high bay is a cost-effective solid state solution for high bay applications, providing a one-for-one replacement of 400 Watt metal halide fixtures.

## FEATURES

- 147 LPW ultra-high efficiency delivers superior performance over older HID high bays
- 0-10V dimming
- Instant-on with no warmup
- 6' power cord standard for more installation flexibility

## LISTINGS

- IP65 Rated
- UL Listed for wet locations
- DesignLights Consortium® 5.1 Premium- meets the requirements for the highest DLC qualification for efficacy and lumen maintenance; DLC PN - PLTSN121422

## PERFORMANCE

- CRI: >80
- CCT: 5000K
- LED L70 Lifetime: 100,000 Hours
- Philips Lumileds LEDs

## THERMAL

- -40°F to 122°F (-40°C to 50°C) operating temperature

## ELECTRICAL

- THD: ≥0.9
- Power Factor: ≤20%
- Input Voltage: 120-277V
- Surge Protection: 4kV
- Dimmable power supply (0-10V)

## INSTALLATION

- Suspended mounting with included 10mm ring or surface mounting with u-bracket (sold separately); see installation instructions for more information
- S/MH(C0/C180): 1.30
- S/MH(C90/C270): 1.28

## CONSTRUCTION

- Slim, lightweight die-cast aluminum construction allows for quick and easy installation

project name	type
catalog number	
comments	voltage
approved by	date



## WARRANTY

- 5 year limited warranty; see [pltsolutions.com](http://pltsolutions.com) for warranty details

## APPLICATIONS

- Warehouses
- Manufacturing Plants
- Distribution Centers
- Grocery Stores
- Gymnasiums
- Indoor Recreational Facilities
- Cold Storage
- Big Box Retail
- Service Repair Centers

# PERFORMANCE SUMMARY

Item #	Model	Watts	Lumens	LPW	CCT	CRI	Dimming	Voltage	Replaces	DLC #	DLC Rating
PLT-11904	UFO	150	22,000	147	5000K	>80	0-10V	120-277V	MH400	PLTSN121422	5.1 Premium

## MOUNTING ACCESSORIES

SKU	Description
PLTS-12378	Adjustable U-Bracket - Black

## DIMENSIONS



### DIMENSIONS

Height: 6"

Diameter: 11.8"

Ring Mount Thread Size: 10MM

## PHOTOMETRICS

