

DesignLights Consortium



Classification	Standard
Primary Use	Direct Linear Ambient Luminaires
Reported Input Wattage	16.9 W
Reported Light Output	1967 lm
Reported CCT	4000 K
Reported CRI (Ra)	80
Product ID	PG2YX8VF
DLC Family Code	PPPRXM
Listing Status	Listed
Date Qualified	2022-03-23

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PG2YX8VF
Manufacturer	Acuity Brands Lighting
Brand	Lithonia Lighting
Model Number	SBL2 LP840
Parent	No
Classification	Standard
DLC Family Code	PPPRXM
Length	2.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Linear Ambient
Primary Use Designation	Direct Linear Ambient Luminaires

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	No Wired Communication Protocol
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	1967 lm
Reported Efficacy (AC)	116.39 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	80
Reported R9	4
Reported IES Rf	82
Reported IES Rg	93
Reported IES Rcs,h1	-13
Reported Default Light Output	1967 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	16.9 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	16.9
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2022-03-23	Listed	5.1	Standard
------------	--------	-----	----------