DesignLights Consortium





Classification	Standard
Primary Use	Direct Linear Ambient Luminaires
Reported Input Wattage	90 W
Reported Light Output	12195 lm
Reported CCT	3500 K
Reported CRI (Ra)	80
Product ID	PLDPSX77A7HK
DLC Family Code	VVVZJR
Listing Status	Listed
Date Qualified	2020-11-05

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting		
Technical Requirements Version	5.1		
Product ID	PLDPSX77A7HK		
Manufacturer	Halco Lighting Technologies		
Brand	ProLED Select		
Model Number	LVPT-8-WS-CS-U-[Blank,EM]-[Blank,MS]		
Parent	No		
Classification	Standard		
DLC Family Code	VVVZJR		
Length	8.0 ft		
Input Power Type	AC		

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	Linear Ambient	
Primary Use Designation	Direct Linear Ambient Luminaires	

PRODUCT CAPABILITIES VIEW DETAILS

Integral Controls	Yes		
Dimming Capability and Range	Continuous Dimming to 10% or below		
Integral Control Capability	No Control Capability		
Sensor Type	Occupancy Sensing		
SSL V5 Wired Communication Protocol	0-10V Analog		
SSL V5 Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	Yes		
White-Tunable	Yes		
Warm-Dimming	No		
Field Adjustable Light Distribution	No		

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	12195 lm
Reported Efficacy (AC)	135.5 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	80
Reported R9	1
Reported IES Rf	84
Reported IES Rg	95
Reported IES Rcs,h1	-13
Reported Minimum Light Output	8340 lm
Reported Maximum Light Output	12195 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	12195 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	90 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	60
Reported Maximum Input Wattage	90
Reported Default Input Wattage	90

Voltage Range	120-277 V
	120-277 V

VERSION HISTORY VIEW DETAILS

2022-04-22	Listed	5.1	Standard
2020-11-05	Listed	5	Premium